

Non-metallic conduit systems

UNEF Type SFA - Adaptalok ATS™

UNEF Type SFA - Adaptalok ATS™

Straight body - Swivel internal female thread / Materials: Polyamide (nylon) 66, aluminium/TPE / Colour: Black (BL) Only / Yellow (Y), Blue (B) Elastomer

	Part no.	Nominal conduit size (mm)	Connector UNEF thread		Part no.	Nominal conduit size (mm)	Connector UNEF thread
	AT13/U063/SFA	13	5/8" - 24		AT21/U144/SFA	21	1 7/16" - 18
	AT13/U075/SFA	13	3/4" - 20		AT21/U175/SFA	21	1 3/4" - 18
	AT13/U088/SFA	13	7/8" - 20		AT28/U088/SFA	28	7/8" - 20
	AT16/U063/SFA	16	5/8" - 24		AT28/U094/SFA	28	1 5/16" - 20
	AT16/U075/SFA	16	3/4" - 20		AT28/U100/SFA	28	1" - 20
	AT16/U081/SFA	16	1 3/16" - 20		AT28/U119/SFA	28	1 3/16" - 18
	AT16/U088/SFA	16	7/8" - 20		AT28/U138/SFA	28	1 5/8" - 18
	AT16/U094/SFA	16	1 5/16" - 20		AT28/U144/SFA	28	1 7/16" - 18
	AT16/U100/SFA	16	1" - 20		AT28/U175/SFA	28	1 3/4" - 18
	AT16/U119/SFA	16	1 3/16" - 18		AT28/U200/SFA	28	2" - 16
	AT16/U131/SFA	16	1 5/16" - 18		AT28/U225/SFA	28	2 1/4" - 16
	AT21/U075/SFA	21	3/4" - 20		AT34/U100/SFA	34	1" - 20
	AT21/U088/SFA	21	7/8" - 20		AT34/U119/SFA	34	1 3/16" - 18
	AT21/U094/SFA	21	1 5/16" - 20		AT34/U144/SFA	34	1 7/16" - 18
	AT21/U100/SFA	21	1" - 20		AT34/U175/SFA	34	1 3/4" - 18
	AT21/U113/SFA	21	1 1/8" - 18		AT34/U200/SFA	34	2" - 16
	AT21/U119/SFA	21	1 3/16" - 18		AT42/U175/SFA	42	1 3/4" - 18
	AT21/U131/SFA	21	1 5/16" - 18		AT42/U200/SFA	42	2" - 16
	AT21/U138/SFA	21	1 3/8" - 18		-	-	-

For coupling to UNEF circular connectors

To order quote part number, body colour & Elastomer colour, e.g. AT16/U063/SFA/BLB

Approvals	Blue Elastomer version only	IP rating	Appropriate conduit	Temperature range
    	Intertek	For use with: Type PA / PR / PADL / PF		Static applications: -50°C to +120°C
		IP40	Yes	Moving applications: -45°C to +120°C
		IP65	Yes	Fitting characteristics
		IP68	Yes (4 bar 30mins)	
		IP69	Yes	

