



Switch fuses


OS200...1250 BS -type




OS200B03P




OS200B04P




OS250B03P



OS400B03P



OS800B03P



OS1250B03P

Front operated switch fuses - Mechanism at the end of the switch

Including terminal bolt kit, a black ON-OFF plastic handle and shaft as standard. The handle is IP65 protected, padlockable in the OFF-position and with door interlock in the ON-position. The shaft is adjustable for a range of installation depths.

Rated current AC-20...23≤ 690V	Rated Power AC-23 400/500/690V [kW]	Fuse Size	No. of poles	Part Number	Product Hierarchy 210002 Order Code
			3	OS200B03P	1SCA022709R9330
			4	OS200B04N2P	1SCA022709R9410
			3	OS250B03P	1SCA022750R6660
			4	OS250B04N2P	1SCA022750R7800
			3	OS315B03P	1SCA022719R0680
			4	OS315B04N2P	1SCA022719R2710
			3	OS400B03P	1SCA022719R0840
			4	OS400B04N2P	1SCA022719R2890
			3	OS630B03P	1SCA022825R5850
			4	OS630B04N2P	1SCA022825R6230
			3	OS800B03P	1SCA022825R7550
			4	OS800B04N2P	1SCA022825R8010
			3	OS1250B03P	1SCA105250R1001
			4	OS1250B04N2P	1SCA105469R1001

N2 = Non-fused switched neutral on the right side
N3 = Include a detachable neutral link integrated into the mechanism

¹⁾ Max. fuse diameter 32 mm
²⁾ AC-23
³⁾ Include a detachable neutral link integrated into the mechanism

Shafts and handles included as standard

Suitable for switches	Included shaft	Included handle	Incl. terminal bolts
OS630...800 _ P	OXp12X280	OHb145J12	M12X40
OS1250 _ P	OXp12X395	OHb274J12	M12X50