

RCCBs

F 200 series A  type, selective



F202



F204



F204 125 A

F 200 A selective type

Function: protection against the effects of sinusoidal alternating and direct pulsating earth fault currents with an intentional tripping delay, which permits to realize the selectivity with downstream instantaneous devices (for more information about selectivity see the technical guide); protection against indirect contacts.

Application: commercial, industrial.

Standard: IEC/EN 61008-1; IEC/EN 61008-2-1

Surge current resistance (wave 8/20)=5000 A

Marking: according to EN 61008-1; EN 61008-2-1

Number of poles	Rated residual current $I_{\Delta n}$ mA	Rated current I_n A	Bbn 8012542 EAN	Order details		Price 1 piece	Weight 1 piece kg	Pack unit pc.
				Type code	Order code			
2	100	40	822905	F202 A S-40/0.1	2CSF202201R2400		0.225	1/6
		63	823001	F202 A S-63/0.1	2CSF202201R2630		0.225	1/6
		100	916000	F202 A S-100/0.1	2CSF202201R2900		0.225	1/6
	300	40	784302	F202 A S-40/0.3	2CSF202201R3400		0.225	1/6
		63	784401	F202 A S-63/0.3	2CSF202201R3630		0.225	1/6
		100	916109	F202 A S-100/0.3	2CSF202201R3900		0.225	1/6
	500	40	784500	F202 A S-40/0.5	2CSF202201R4400		0.225	1/6
		63	784609	F202 A S-63/0.5	2CSF202201R4630		0.225	1/6
		100	916208	F202 A S-100/0.5	2CSF202201R4900		0.225	1/6
	1000	40	823100	F202 A S-40/1	2CSF202201R5400		0.225	1/6
		63	823209	F202 A S-63/1	2CSF202201R5630		0.225	1/6
		100	916307	F202 A S-100/1	2CSF202201R5900		0.225	1/6

Number of poles	Rated residual current $I_{\Delta n}$ mA	Rated current I_n A	Bbn 8012542 EAN	Order details		Price 1 piece	Weight 1 piece kg	Pack unit pc.
				Type code	Order code			
4	100	40	823308	F204 A S-40/0.1	2CSF204201R2400		0.375	1/3
		63	823407	F204 A S-63/0.1	2CSF204201R2630		0.375	1/3
		100	919001	F204 A S-100/0.1	2CSF204201R2900		0.405	1/3
	300	40	784708	F204 A S-40/0.3	2CSF204201R3400		0.375	1/3
		63	784807	F204 A S-63/0.3	2CSF204201R3630		0.375	1/3
		100	919100	F204 A S-100/0.3	2CSF204201R3900		0.405	1/3
	500	125	968207	F204 A S-125/0.3	2CSF204201R3950		0.500	1
		40	784906	F204 A S-40/0.5	2CSF204201R4400		0.375	1/3
		63	785002	F204 A S-63/0.5	2CSF204201R4630		0.375	1/3
	1000	100	919209	F204 A S-100/0.5	2CSF204201R4900		0.405	1/3
		125	968405	F204 A S-125/0.5	2CSF204201R4950		0.500	1
		40	823506	F204 A S-40/1	2CSF204201R5400		0.375	1/3
		63	823605	F204 A S-63/1	2CSF204201R5630		0.375	1/3
		100	919308	F204 A S-100/1	2CSF204201R5900		0.405	1/3