

PRODUCT-DETAILS

CT-TGD.12

CT-TGD.12 Time relay, pulse generator 1c/o, 24-240VAC 24-48VDC



General Information

Extended Product Type	CT-TGD.12
Product ID	1SVR500160R0000
EAN	4013614350696
Catalog Description	CT-TGD.12 Time relay, pulse generator 1c/o, 24-240VAC 24-48VDC
Long Description	The CT-TGD.12 is a single-function electronic time relay from the CT-D timer range. It provides a pulse generator (recycling unequal times) function with 2x7 time ranges from 0.05 s to 100 h. This time relay operates with a rated control supply voltage of 24 - 48 V DC / 24 - 240 V AC and has a 1 c/o (SPDT) output rated at 250 V / 4 A. A control input works with voltage-related (non-floating) triggering.

Ordering

EAN	4013614350696
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	89 mm
Package Level 1 Depth / Length	20 mm
Package Level 1 Height	65 mm
Package Level 1 Gross Weight	0.065 kg

Package Level 1 EAN

4013614350696

Dimensions

Product Net Width	17.5 mm
Product Net Height	70 mm
Product Net Depth / Length	63 mm
Product Net Weight	0.052 kg

Technical

Timer Relay Type	Pulse Generator
Time Range	0.05 s ... 100 h
Rated Control Supply Voltage (U _s)	24 ... 240 V AC 24 ... 48 V DC
Output	1 c/o (SPDT) contact
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 6 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 6 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Connecting Capacity	Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Tightening Torque	0.5 ... 0.8 N·m
Wire Stripping Length	7 mm
Mounting Position	Any
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 EN 50581 IEC/EN 61812-1 UL 508

Environmental

Ambient Air Temperature	Operation -20 ... +60 °C Storage -40 ... +85 °C
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	C300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG

	Rigid 2x 20-16 AWG
Tightening Torque	4.43 ... 7.08 in-lb
UL/CSA	

Certificates and Declarations (Document Number)

CB Certificate	CB_DK-8574
CCC Certificate	CCC_2019010303150608
cULus Certificate	cULus508_20180410-E140448
Data Sheet, Technical Information	2CDC111157D0201
Declaration of Conformity - CE	1SVD981010-0001
EAC Certificate	EAC_RU_C-DE.ME77.B.02016
Environmental Information	1SAA981011-2402
Instructions and Manuals	1SVC500010M1000
RMRS Certificate	RMRS_1740021250
RoHS Information	1SVD981010-0001

Classifications

Object Classification Code	K
ETIM 4	EC001439 - Timer relay
ETIM 5	EC001439 - Timer relay
ETIM 6	EC001439 - Timer relay
ETIM 7	EC001439 - Timer relay
eClass	7.0 27371790
UNSPSC	39121519

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Time Relays

