

K6, KC6 4-pole mini contactor relays

Accessories



CAF6-11K

2CDC211019F0011



CA6-11K

2CDC211009F0010



CA6-11K-P

2CDC211011F0010



CA6-11K-F

2CDC211010F0010



LT6-B

2CDC211006F0010



RV-BC6/250

2CDC211007F0010

Suitable for	Auxiliary contacts	Type	Order code	Pkg qty	Weight (1 pce)
					kg

Front mounted instantaneous auxiliary contact blocks (1)

K6, KC6	1 1	CAF6-11K	GJL1201330R0001	10	0.020
	2 0	CAF6-20K	GJL1201330R0005	10	0.020
	0 2	CAF6-02K	GJL1201330R0009	10	0.020

Side mounted instantaneous auxiliary contact block (1)

K6, KC6	1 1	CA6-11K	GJL1201317R0001	10	0.030
---------	-----	---------	-----------------	----	-------

Side mounted instantaneous auxiliary contact block with soldering pins (2)

K6..P, KC6..P	1 1	CA6-11K-P	GJL1201319R0001	10	0.025
---------------	-----	-----------	-----------------	----	-------

Side mounted instantaneous auxiliary contact block with flat pin connection (2)

K6..F, KC6..F	1 1	CA6-11K-F	GJL1201318R0001	10	0.025
---------------	-----	-----------	-----------------	----	-------

Soldering socket (Ie < 8 A)

K6, KC6	LB6	GJL1201902R0001	10	0.020
2-pole auxiliary contact blocks CA	LB6-CA	GJL1201903R0001	10	0.010

(1) CA6 and CAF6 must not be fitted simultaneously.

Suitable for	Rated control circuit voltage UC V DC	Connection type	Type	Order code	Pkg qty	Weight (1 pce)
						kg

Surge suppressors for contactor coils

KC6	24 ... 60	Cable lug	RV-BC6/60	GHV2501902R0002	10	0.005
	50 ... 250	Cable lug	RV-BC6/250	GHV2501903R0002	10	0.005

Note: Mini contactors for AC operation have an integrated protective circuit

Cover cap, transparent fitting to DIN rail design, sealable

K6, KC6	LT6-B	GJL1201906R0001	10	0.015
---------	-------	-----------------	----	-------