

Pluggable interface relays and optocouplers

Selection table CR-M range

CR-M pluggable relays with LED

	Type	Order code
	CR-M012DC2L	1SVR405611R4100
	CR-M012DC2LD	1SVR405611R4400
	CR-M024DC2L	1SVR405611R1100
	CR-M024DC2LD	1SVR405611R1400
	CR-M048DC2L	1SVR405611R6100
	CR-M048DC2LD	1SVR405611R6400
	CR-M060DC2L	1SVR405611R4300
	CR-M110DC2L	1SVR405611R8100
	CR-M110DC2LD	1SVR405611R8400
	CR-M125DC2L	1SVR405611R8300
	CR-M125DC2LD	1SVR405611R8500
	CR-M220DC2L	1SVR405611R9100
	CR-M220DC2LD	1SVR405611R9400
	CR-M012AC2L	1SVR405611R0300
	CR-M024AC2L	1SVR405611R0300
	CR-M048AC2L	1SVR405611R5100
	CR-M110AC2L	1SVR405611R7100
	CR-M120AC2L	1SVR405611R2100
	CR-M230AC2L	1SVR405611R3100
Input voltage		
12 V DC	■	■
24 V DC		■
48 V DC		■
60 V DC		■
110 V DC		■
125 V DC		■
220 V DC		■
12 V AC		■
24 V AC		■
48 V AC		■
60 V AC		■
110 V AC		■
120 V AC		■
230 V AC		■
Output rating		
250 V 6 A		
250 V 10 A		
250 V 12 A	■	■
Output contacts		
c/o	2	2
Gold plated contacts		
Additional features		
LED	■	■
Free-wheeling diode	■	■