



Main

Range of product	TeSys
Product name	TeSys island
Device short name	TPRPM
Product or component type	Power module
Device presentation	Power module connected to an automation controller through a bus coupler Operational only when connected to a bus coupler
Function available	Upstream voltage presence detection Electronic thermal overload protection Monitoring of currents Control of third party power devices when associated to TPRDG IO module
Product compatibility	TPRBC bus coupler TPRDG digital IO module TPRAN analog IO module
Poles description	3P
Motor power kW	2.2 kW at 230 V AC 50 Hz 4 kW at 380...415 V AC 50 Hz 4 kW at 440 V AC 50 Hz 5.5 kW at 500 V AC 50 Hz 5.5 kW at 690 V AC 50 Hz
Motor power HP (UL / CSA)	0.33 hp at 120 V AC 60 Hz for 1 phase motors 1 hp at 240 V AC 60 Hz for 1 phase motors 2 hp at 208 V AC 60 Hz for 3 phases motors 2 hp at 240 V AC 60 Hz for 3 phases motors 5 hp at 480 V AC 60 Hz for 3 phases motors 7.5 hp at 600 V AC 60 Hz for 3 phases motors
[Ue] rated operational voltage	<= 690 V AC 47...63 Hz
[Ie] rated operational current	9 A (at <50 °C) at <= 440 V AC-3 15 A (at <50 °C) at <= 440 V AC-1
[Ith] conventional free air thermal current	15 A (at 50 °C)
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1 600 V conforming to UL 60947-4-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

600 V conforming to CSA C22.2 No 60947-4-1

[Uimp] rated impulse withstand voltage	6 kV
Overvoltage category	III
Thermal protection adjustment range	0.18...9 A
Thermal overload class	Class 5...30
Reset	Remotely or automatically
[Uc] control circuit voltage	24 V DC supplied by the bus coupler
Current consumption	60 mA
Power dissipation in W	0.6 W at Ie AC-3

Complementary

Protection type	Thermal overload protection Motor overheat Overcurrent Undercurrent Jam Long start Stall Rapid cycle lockout Phase loss Rapid restart lockout Phase reversal Phase unbalance Phase sequence Ground current
Monitoring type	Time device ON Number of faults Number of device power cycles Average current Iavg Average voltage Vavg Max current Imax Max voltage Vmax
Local signalling	1 LED (green/red) for DS (device status) 1 LED (green/red) for LS (load status)
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	CCC CSA EAC UL
Mounting mode	Horizontal and vertical (35 mm symmetrical DIN rail)
Connections - terminals	Screw-clamp terminals 1 cable(s) 1...4 mm ² (AWG 16...AWG 12) rigid Screw-clamp terminals 2 cable(s) 1...4 mm ² (AWG 16...AWG 12) rigid Screw-clamp terminals 1 cable(s) 1.5...4 mm ² (AWG 16...AWG 12) flexible without cable end Screw-clamp terminals 2 cable(s) 1.5...4 mm ² (AWG 16...AWG 12) flexible without cable end Screw-clamp terminals 1 cable(s) 1...4 mm ² (AWG 16...AWG 12) flexible with cable end Screw-clamp terminals 2 cable(s) 1...2.5 mm ² (AWG 16...AWG 14) flexible with cable end
Tightening torque	1.7 N.m - with screwdriver flat Ø 6 mm 1.7 N.m - with screwdriver Philips No 2
Width	45 mm
Height	121 mm
Depth	115 mm
Net weight	0.255 kg

Environment

Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-10...50 °C without derating 50...60 °C with current derating
Relative humidity	5...95 %
Operating altitude	0...2000 m without derating

IP degree of protection	IP20
Pollution degree	2
Protective treatment	TC
Fire resistance	960 °C conforming to UL 94 850 °C conforming to IEC 60695-2-1 650 °C conforming to IEC 60695-2-12
Shock resistance	15 gn (duration = 11 ms) conforming to IEC 60068-2-27
Vibration resistance	1.5 mm peak to peak (f= 3...13 Hz) conforming to IEC 60068-2-6 1 gn (f= 13...200 Hz) conforming to IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge immunity test, level 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF field immunity test, level 3, 10 V/m, conforming to EN/IEC 61000-4-3 Fast transient immunity test, level 4, 4 kV, conforming to EN/IEC 61000-4-4 Surge immunity test (differential mode), level 3, 2 kV, conforming to EN/IEC 61000-4-5 Surge immunity test (common mode), level 4, 4 kV, conforming to EN/IEC 61000-4-5 Conducted RF disturbance immunity test, 20 V, conforming to EN/IEC 61000-4-6

Packing Units

Package 1 Weight	278.000 g
Package 1 Height	11.500 cm
Package 1 width	4.500 cm
Package 1 Length	12.000 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product