

16	110	50 - 60	1216	4	1219	4	1225	4
	240	50 - 60	1217	6	1220	9	1226	9
	415	50 - 60	1218	9	1221	6	1227	6
32	110	50 - 60	1228	4	1231	4	1237	4
	240	50 - 60	1229	6	1232	9	1238	9
	415	50 - 60	1230	9	1233	6	1239	6



Panel Mounting Socket Outlet

Splashproof

20° Angle

63	110	50 - 60	12134	4	12137	4	12138	4
	240	50 - 60	12135	6	1207	9	1208	9
	415	50 - 60	12136	9	1201	6	1202	6



Panel Mounting Socket Outlet

Splashproof

15° Angle

16	110	50 - 60	130	4	13015	4		
	240	50 - 60	131	6	13016	9		
	415	50 - 60	132	9	13017	6		



Panel Mounting Socket Outlet

Splashproof

Straight

16	110	50 - 60	1310	4	1313	4	1319	4
	240	50 - 60	1311	6	1314	9	1320	9
	415	50 - 60	1312	9	1315	6	1321	6

Note: 1310 & 1311 are the popular versions



Panel Mounting Socket Outlet

Splashproof

Straight

16	110	50 - 60	13000	4	1322	4	13003	4
	240	50 - 60	13001	6	1323	9	13004	9
	415	50 - 60	13002	9	1324	6	13005	6
32	110	50 - 60	13006	4	13009	4	1331	4
	240	50 - 60	13007	6	13010	9	1332	9
	415	50 - 60	13008	9	13011	6	1333	6



Panel Mounting Socket Outlet

Splashproof

Straight Flange 75 x 75 mm

63	110	50 - 60	1306	4	1309	4	13140	4
	240	50 - 60	1307	6	1304	9	1305	9
	415	50 - 60	1308	9	134	6	136	6



Panel Mounting Socket Outlet

Splashproof


Straight

16A and 32A with screw terminals

63A with screw / clamp terminals and pilot contact

Note: This pilot contact should **NOT** be counted as a main 'pin'

Dimensions




Amperes	16			32		
Poles	3	4	5	3	4	5
a	74	100	100	100	100	100
b	62	92	92	92	92	92
c	60	85	85	85	85	85
d	52	77	77	77	77	77
e	5,5	5,5	5,5	5,5	5,5	5,5
f	8	8	8	8	8	8
h	30	30	29	50	50	50
i	48	50	55	62	62	62
k	57	65	70	75	75	78
l	52	65	70	75	75	78
a	20°	20°	20°	20°	20°	20°
Conductor mm ² min	1,5	1,5	1,5	2,5	2,5	2,5
Conductor mm ² max	4	4	4	10	10	10

Panel Mounting Socket Outlet

20° Angle



Splashproof




Amperes	63		
Poles	3	4	5
a	114	114	114
b	114	114	114
c	90	90	90
d	90	90	90
e	6,5	6,5	6,5
f	12	12	12
h	65	65	65
i	67,5	67,5	67,5
l	92	92	92
Conductor mm ² min	6	6	6
Conductor mm ² max	25	25	25

Panel Mounting Socket Outlet

15° Angle temperature resistant contact-carrier



Splashproof




Amperes	16	
Poles	3	4
a	56	60
b	56	60
c	44	50-52
d	44	50-52
e	4,4	5,5
f	7	7
h	17	26
i	51	53
k	70	80
l	45	45
m	13	9
Conductor mm ² min	1,5	1,5
Conductor mm ² max	4	4

Panel Mounting Socket Outlet



Splashproof




Amperes	16	
Poles	3	4
a	62	72
b	62	65
c	47	52
d	47	52
e	5,5	5,5
f	7	7
h	17	26
i	51	53
k	70	80
l	45	45
m	10	9
Conductor mm ² min	1,5	1,5
Conductor mm ² max	4	4

Panel Mounting Socket Outlet



Splashproof




Amperes	16			32		
Poles	3	4	5	3	4	5
a	75	75	75	75	75	75
b	75	75	75	75	75	75
c	60	60	60	60	60	60
d	60	60	60	60	60	60
e	5,5	5,5	5,5	5,5	5,5	5,5
f	7	7	7	8	8	8
h	17	26	17	36	36	19
i	51	53	53	62	62	62
k	70	80	85	90	90	98
l	45	45	55	60	60	60
m	3,5	7	11,5	12	12	17
Conductor mm ² min	1,5	1,5	1,5	2,5	2,5	2,5
Conductor mm ² max	4	4	4	10	10	10

Panel Mounting Socket Outlet



Splashproof



Amperes	63		
Poles	3	4	5
a	107	107	107
b	100	100	100
c	85	85	85
d	77	77	77
e	6,5	6,5	6,5
f	12	12	12
h	56	56	56
i	77	77	77
k	110	110	110
l	88	88	88
m	7	7	7
Conductor mm ² min	6	6	6
Conductor mm ² max	25	25	25

Panel Mounting Socket Outlet

Temperature resistant contact-carrier



Splashproof