

Viking 3 heavy duty terminal blocks
for copper bars and cable lugs



0390 32



0394 78 + 86

 Technical characteristics **p. 135**

Pack	Cat. Nos.	Heavy duty terminal blocks			
		For copper bars or cable lugs			
		Conform to IEC EN 60947-7-1			
		Fire resistance : 960 °C, IEC EN 60695-2-11			
		V2 according to UL94			
		Insulating material : polyamide -30 °C to +100 °C			
		Bridging the gap between the enclosure and external cables			
		Plastic foot			
		For use with terminal marker sheets (p. 140)			
		Separation barriers and protective covers to be ordered separately			
		For symmetrical rails			
		Fixed using metal clip on rails  15 mm depth and  EN 60715, 15 mm depth (p. 126)			
		Connecting max. (mm²)	Width of plate (mm)	Stud (Ø)	Width (mm)
5	0390 71	35	15	M 8	26
5	0390 72	70	20	M 10	34
5	0390 73	120	25	M 10	34
5	0390 74	240	35	M 12	46
		For asymmetrical rails			
		Fixed using metal clip on rails  EN 60715 (p. 26)			
5	0390 31	35	15	M 8	26
5	0390 32	70	20	M 10	34
5	0390 33	120	25	M 10	34
5	0390 34	240	35	M 12	46

Pack	Cat. Nos.	Accessories	
		Separation barriers	
		Take protective covers	
		Marking possible with CAB 3 marking system (p. 140)	
10	0394 77	For terminals with width 26 mm	
10	0394 78	For terminals with width 34 and 46 mm	
		Protective covers	
		For mounting on separation barriers	
5	0394 86	For 3 terminals with width 46 mm or for 4 terminals with width 34 mm	
5	0394 88	For 4 terminals with width 26 mm	
5	0394 89	For 4 terminals with width 46 mm	



End stops p. 126

 CAB 3 marking system **p. 140-142**



 Enclosures **p. 14-23**

