


Plexo³

IP 65 weatherproof enclosures and accessories


■ Dimensions

Enclosures 2, 4, 6 and 8 modules



Cat. Nos.	Dimensions (mm)				
	A	B	C	D	E
6019 32	109	93	174	94	—
6019 74	115.6	128	200	120	—
6019 76	115.6	164	200	120	70
6019 78	115.6	200	200	120	106

Enclosures 12 and 18 modules



Cat. Nos.	Dimensions (mm)				
	A	B	C	D	E
6019 81	141	340	282	180	180
6019 82	161	340	432	330	180
6019 83	161	340	622	480	180
6019 85	141	448	282	180	288
6019 86	161	448	432	330	290
6019 87	161	448	622	480	290
6019 88	161	448	822	680	290


■ Fixing centres

Fixing the enclosure on the wall

Each enclosure is equipped with knockout entries for 2 wall-fixing methods :


Hanging fixing

1 point in the middle, 2 points at the bottom



Adjustable peripheral fixing

4 fixing points



■ Number of knockouts on each side

Cat. Nos.	Top/bottom			Left/right		
	Ø20 mm	Ø25 mm	Ø32 mm	Ø20 mm	Ø25 mm	Ø32 mm
6019 32	2	—	—	—	—	—
6019 74	2	1	—	2	—	—
6019 76	4	1	—	2	—	—
6019 78	6	1	—	2	—	—
6019 81	7	2	2	—	—	2
6019 82	13	2	2	—	—	3
6019 83	13	2	2	—	—	4
6019 85	12	2	3	—	—	2
6019 86	13	4	3	—	—	3
6019 87	13	4	3	—	—	4
6019 88	13	4	3	—	—	5

■ Old/new range cross reference table

Old Plexo Cat. Nos.	New Plexo ³ Cat. Nos.	Number of rows	Total number of modules
Enclosures 2 to 8 modules			
0017 02	6019 32	1	2 (+1)
0017 04	6019 74	1	4
0017 06	6019 76	1	6
0017 08	6019 78	1	8
Enclosures 12 modules per row			
0017 11	6019 81	1	12
0017 12	6019 82	2	24
0017 13	6019 83	3	36
Enclosures 18 modules per row			
—	6019 85	1	18
—	6019 86	2	36
—	6019 87	3	54
—	6019 88	4	72

■ Direct piercing end caps

Cat. No.	Type	Number of end caps per pack	Ø	
			Min. (mm)	Max. (mm)
0019 55	ISO 20	10	4	13
	ISO 25	5	9	18
	ISO 32	2	12	25