

Hypra® IP 66/67-55 - LV 32 A

plastic plugs and sockets



0530 50 + 0529 40

Technical information and dimensions **p. 171-173**
Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS 60309-2, IEC 60309-1 and IEC 60309-2
IP according to BS EN 60529 and IEC 60529

IK 09

Self-extinguishing : 850 °C for insulated parts, 650 °C for housing

Stainless steel external screws - Nickel plated brass contacts

Temp. rating : -50 °C to +100 °C

Pack Cat. Nos. Panel mounting sockets (modular) 32 A

Pack	Cat. Nos.	
1	Modular 0530 46	200 to 250 V~ 2 P + $\perp$
1	0530 50	380 to 415 V~ 3 P + $\perp$
1	0530 51	3 P + N + $\perp$

Pack	Cat. Nos.	
1	0530 76	200 to 250 V~ 2 P + $\perp$
1	0530 80	380 to 415 V~ 3 P + $\perp$
1	0530 81	3 P + N + $\perp$

Pack	Cat. Nos.	
1	0530 56	200 to 250 V~ 2 P + $\perp$
1	0530 60	380 to 415 V~ 3 P + $\perp$
1	0530 61	3 P + N + $\perp$

Pack	Cat. Nos.	
1	0530 06	200 to 250 V~ 2 P + $\perp$
1	0530 10	380 to 415 V~ 3 P + $\perp$
1	0530 11	3 P + N + $\perp$

Back boxes

Pack	Cat. Nos.	
1	0529 40	Surface mounting boxes For LV 32 A 2 P + $\perp$ / 3 P + $\perp$ / 3 P + N + $\perp$ sockets
1	0529 90	Through entry surface mounting boxes For LV 32 A 2 P + $\perp$ / 3 P + $\perp$ / 3 P + N + $\perp$ sockets

Hypra® IP 66/67-55 - LV 63 and 125 A

plastic plugs and sockets



0594 27



0595 32

Technical information and dimensions **p. 171-173**
Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS 60309-2, IEC 60309-1 and IEC 60309-2
IP according to BS EN 60529 and IEC 60529

IK 09

Self-extinguishing : 850 °C for insulated parts, 650 °C for housing

Stainless steel external screws - Nickel plated brass contacts

Temp. rating : -50 °C to +100 °C

LV 63 A and 125 A have a pilot pin

Pack Cat. Nos. Panel mounting sockets 63 and 125 A

Pack	Cat. Nos.	
1	63 A 125 A 0594 27 0595 12	380 to 415 V~ 3 P + $\perp$
1	0594 28 0595 13	3 P + N + $\perp$

Surface mounting sockets 63 and 125 A

Pack	Cat. Nos.	
1	63 A 125 A 0594 37 0595 02	380 to 415 V~ 3 P + $\perp$
1	0594 38 0595 03	3 P + N + $\perp$

Mobile sockets 63 and 125 A

Pack	Cat. Nos.	
1	63 A 125 A 0594 87 0595 32	380 to 415 V~ 3 P + $\perp$
1	0594 88 0595 33	3 P + N + $\perp$

Straight plugs 63 and 125 A

Pack	Cat. Nos.	
1	63 A 125 A 0594 47 0595 22	380 to 415 V~ 3 P + $\perp$
1	0594 48 0595 23	3 P + N + $\perp$