



NHDC406006P

NHDC405004P

DC ISOLATOR

DC Isolator in an all insulated enclosure with rotary handle and padlock locking Off facility.

- Multi Pole
- 25A, 32A, 40A
- 500V or 600V DC
- Insulated Enclosure
- Rotary Handle & padlock 'Off' facility
- DC - 21B utilization category

CAT REF.	DESCRIPTION
NHDC325004P	32A 500V 4 Pole
NHDC405004P	40A 500V 4 Pole
NHDC256006P	25A 600V 6 Pole
NHDC406006P	40A 600V 6 Pole



NHTPSD32

NHTPSD25

AC ISOLATOR

AC Isolator in an all insulated IP65 enclosure with rotary door interlock and padlock locking Off facility.

- Multi Pole
- 16, 25 or 32A, AC 21 & AC 23 rated
- 230V AC
- IP65 Enclosure
- Rotary Handle & padlock 'Off' facility

CAT REF.	DESCRIPTION
NHTPSD16	16A 230V AC 3 Pole
NHTPSD25	25A 230V AC 3 Pole
NHTPSD32	32A 230V AC 3 Pole



NHSPMTRA

NHSPMTRD

MID METERS IN ENCLOSURE

MID B&D certified meters c/w an IP40 insulated enclosure.

- Direct connected kWh meter
- Mechanical barell number or Liquid Crystal Display
- Pulsed output for BMS monitoring
- DIN Rail mounting

CAT REF.	DESCRIPTION
NHSPMTRA	1 Mod MID Meter (Analogue)
NHSPMTRD	1 Mod MID Meter (Digital)

Note: Surge Protection devices and Type B RCDs are available on request

For PV Installation Requirements see page 60/61.