

# Hypra® IP 66/67-55 - LV 16 A

## plastic plugs and sockets



Technical information and dimensions **p. 171-173**  
Conformity to International Standards **p. 198**

Conform to BS EN 60309-1, BS EN 60309-2, IEC 60309-1 and IEC 60309-2  
IP according to BS EN 60529 and IEC 60529  
IK 09  
Self-extinguishing : 850 °C for insulated parts, 650 °C for housing  
Stainless steel external screws - Nickel plated brass contacts  
Temp. rating : -50 °C to +100 °C

| Pack  | Cat. Nos. |         | Panel mounting sockets 16 A                                                                                                        |
|-------|-----------|---------|------------------------------------------------------------------------------------------------------------------------------------|
|       | Plastic   | Modular | Plastic version can be used with back boxes to create surface mounting sockets (modular version is not compatible with back boxes) |
| 1     | 0511 25   |         | <b>100 to 130 V~</b><br>2 P + $\perp$                                                                                              |
| 5   1 | 0511 26   | 0511 46 | <b>200 to 250 V~</b><br>2 P + $\perp$                                                                                              |
| 1     | 0511 30   | 0511 50 | <b>380 to 415 V~</b><br>3 P + $\perp$                                                                                              |
| 1     | 0511 31   | 0511 51 | 3 P + N + $\perp$                                                                                                                  |

| Pack | Cat. Nos. |  | Mobile sockets 16 A                   |
|------|-----------|--|---------------------------------------|
| 1    | 0511 75   |  | <b>100 to 130 V~</b><br>2 P + $\perp$ |
| 1    | 0511 76   |  | <b>200 to 250 V~</b><br>2 P + $\perp$ |
| 1    | 0511 80   |  | <b>380 to 415 V~</b><br>3 P + $\perp$ |
| 1    | 0511 81   |  | 3 P + N + $\perp$                     |

| Pack | Cat. Nos. | Straight plugs 16 A                   |
|------|-----------|---------------------------------------|
| 1    | 0511 55   | <b>100 to 130 V~</b><br>2 P + $\perp$ |
| 1    | 0511 56   | <b>200 to 250 V~</b><br>2 P + $\perp$ |
| 5    | 0511 60   | <b>380 to 415 V~</b><br>3 P + $\perp$ |
| 5    | 0511 61   | 3 P + N + $\perp$                     |

| Pack | Cat. Nos. | Angled plugs 16 A                     |
|------|-----------|---------------------------------------|
| 1    | 0511 06   | <b>200 to 250 V~</b><br>2 P + $\perp$ |
| 1    | 0511 10   | <b>380 to 415 V~</b><br>3 P + $\perp$ |
| 1    | 0511 11   | 3 P + N + $\perp$                     |

| Pack | Cat. Nos. | Back boxes                                                                       |
|------|-----------|----------------------------------------------------------------------------------|
| 5    | 0520 29   | <b>Surface mounting boxes</b><br>For LV 16 A 2 P + $\perp$ sockets               |
| 5    | 0522 29   | For LV 16 A 3 P + $\perp$ / 3 P + N + $\perp$ sockets                            |
| 1    | 0520 89   | <b>Through entry surface mounting boxes</b><br>For LV 16 A 2 P + $\perp$ sockets |
| 5    | 0522 89   | For LV 16 A 3 P + $\perp$ / 3 P + N + $\perp$ sockets                            |