

RCBOs DX™ 10000

residual current circuit breakers from 10 A to 45 A - AC type



6064 15

Dimensions p. 65
 Technical information p. 59-60

Breaking capacity:
 10000 - IEC 61009-1 for single pole
 • AC type : detect AC component faults

Pack	Cat. Nos.	Single pole - 230 V~ - C curve		
		Blue neutral leads		
		AC Type 30 mA	Nominal rating In (A)	Number of modules
		C curve		
1	6064 10		10	1
1	6064 11		16	1
1	6064 12		20	1
1	6064 13		25	1
1	6064 14		32	1
1	6064 15		45	1

RCBOs DX³ 6000 - 10 kA

NEW

residual current circuit breakers from 3 A to 63 A - AC type



4110 02

Dimensions p. 65
 Technical information p. 59-60

Conform to IEC 61009-1
 Breaking capacity:
 6000 - IEC 61009-1 - 10 kA / IEC 60947-2 for single pole + neutral, double and four pole
 • AC type : detect AC component faults
 Enhanced immunity to unwanted tripping in disturbed environments
 Can be equipped with DX³ auxiliaries and accessories p. 64

Pack	Cat. Nos.	Single pole + neutral - 230 V~ - B curve		
		Neutral on right-hand side		
		AC Type 30 mA	Nominal rating In (A)	Number of modules
		B curve		
1	4109 18		6	2
1	4110 19		10	2
1	4110 21		16	2
1	4110 22		20	2
1	4110 24		32	2
1	4110 25		40	2

NEW
 Available January 2015

Pack	Cat. Nos.	Single pole + neutral - 230 V~ - C curve		
		Neutral on right-hand side		
		AC Type 10 mA	Nominal rating In (A)	Number of modules
		C curve		
1	4109 93		16	2
		AC Type 30 mA		
1	4109 97		3	2
1	4109 99		6	2
1	4110 00		10	2
1	4110 02		16	2
1	4110 03		20	2
1	4110 04		25	2
1	4110 05		32	2
1	4110 06		40	2
		AC Type 300 mA		
1	4110 21		6	2
1	4110 22		10	2
1	4110 24		16	2
1	4110 25		20	2
1	4110 26		25	2
1	4110 27		32	2
1	4110 28		40	2