

Atlantic metal enclosures

IP 55/IP 66 - IK 10 - Type 4x - Type 12



0369 19



0369 28



0369 79



0355 53



Enclosure and equipment selection chart **p. 8-9**
Technical characteristics **p. 12**

IP 66 according to standards IEC EN 60529 for 1-door enclosures - IP 55 according to standards IEC EN 60529 for 2-door enclosures
IK 10 according to standards IEC EN 62262

LCIE 17 07 90 10A

Type 4x, 1 door, Type 12, 2 doors - cULus, Bureau Veritas

EMC attenuation 20 dB (for an EMC attenuation from 40 to 50 dB at 1 GHz, please consult us)

Excellent resistance to corrosion and chemical agents

80 µm thick textured polyester coating. Anti-corrosion treatment for hinges and pins

Reversible door - Fitted with lever

Double bar lock - Self-centering positioning system for the equipment

Compatible with all Atlantic accessories

Low cable entries RAL 7035 - Optional depth adjustment for enclosures 400 mm depth, with side rails Cat. No. 0367 45 (p. 11)

Pack	Cat. Nos.		Metal enclosures		
			Vertical version		
			External dimensions (mm) Height x Width x Depth	Number of doors	Weight (kg)
		NEW			
		Metal door	Glass door		
1	0369 10 ¹		300 x 200 x 160	1	3.9
1	0369 12 ¹		400 x 300 x 160	1	6.3
1	0369 13		500 x 400 x 160	1	10.3
1	0369 17	0369 27	400 x 300 x 200	1	6.9
1	0369 18	0369 28	500 x 400 x 200	1	11.2
1	0369 19	0369 29	600 x 400 x 200	1	13
1	0369 20		600 x 500 x 200	1	16.8
1	0369 21		700 x 500 x 200	1	20.3
1	0369 25		500 x 400 x 250	1	13.2
1	0369 26	0369 36	600 x 400 x 250	1	14
1	0369 30	0369 40	700 x 500 x 250	1	23.8
1	0369 31	0369 41	800 x 600 x 250	1	30.9
1	0369 32		1000 x 600 x 250	1	44.5
1	0369 33		1000 x 800 x 250	1	49.5
1	0369 37	0369 47	800 x 600 x 300	1	32
1	0369 38	0369 48	1000 x 600 x 300	1	45
1	0369 39	0369 49	1000 x 800 x 300	1	56.9
1	0369 42		1200 x 600 x 300	1	50.4
1	0369 43		1200 x 800 x 300	1	67
1	0369 44		800 x 600 x 400	1	41.6
1	0369 45		1000 x 800 x 400	1	63.5
1	0369 46	0369 56	1200 x 800 x 400	1	73.6
1	0369 50	0369 60	1400 x 800 x 400	1	81.6
			Square version		
1	0369 51 ¹		300 x 300 x 160	1	4.8
1	0369 55		300 x 300 x 200	1	5.6
1	0369 57		400 x 400 x 200	1	8.7
1	0369 59		500 x 500 x 200	1	13.6
1	0369 62		500 x 500 x 250	1	15.2
1	0369 64	0369 74	600 x 600 x 250	1	22.8
1	0369 68		800 x 800 x 300	1	48
1	0369 72		600 x 600 x 400	1	33.5
			Horizontal version		
1	0369 11 ¹		300 x 400 x 160	1	6.2
1	0369 75		300 x 400 x 200	1	6.9
1	0369 76		400 x 600 x 200	1	13
1	0369 77		400 x 600 x 250	1	14
1	0369 78		600 x 800 x 300	2	38.4
1	0369 79		600 x 1000 x 300	2	47.4
1	0369 80		800 x 1000 x 300	2	59.7
1	0369 81		1000 x 1200 x 300	2	85.7

1: Without cable entries plate

Pack	Cat. Nos.		Roofs RAL 7035		
			Steel		
			Possible adjustment ± 20 mm (front or back)		
			For enclosures		
			Width (mm)	Depth (mm)	Weight (kg)
1	0365 51		300	200	1.2
1	0365 52		400	200	1.4
1	NEW 0365 67		500	200	1.8
1	0365 68		600	200	2.1
1	0365 53		400	250	1.8
1	0365 64		500	250	2
1	0365 54		600	250	2.5
1	0365 56		600	300	3
1	0365 57		800	300	3.6
			Plinths RAL 7021		
			Height 200 mm		
			Front and rear trap door		
			For enclosures		
			Width (mm)	Depth (mm)	Weight (kg)
1	0363 00		600	300	6
1	0363 01		800	300	6.7



Door contact
p. 18



Lina 12.5 and Lina 25 perforated
plates, **p. 16**

