

P 17 Tempra Pro IP 66/67 - LV 16 and 32 A

sockets, plugs, mobile sockets and appliance inlets



5554 14



5553 28

Technical characteristics p. 19

Pack	Cat. Nos.		Surface mounting sockets
	16 A	32 A	Two possible angles (5° or 25°)
5	5553 51	5554 51	100/130 V~ 2 P + ⊥
			200/250 V~
5	5553 54	5554 54	2 P + ⊥
5	5553 55	5554 55	3 P + ⊥
5	5553 56	5554 56	3 P + N + ⊥
			380/415 V~
5	5553 58	5554 58	3 P + ⊥
5	5553 59	5554 59	3 P + N + ⊥
			Panel mounting sockets inclined outlet
			Can be fixed on faceplates (p. 18)
5	16 A 5553 81	32 A 5554 81	100/130 V~ 2 P + ⊥
			200/250 V~
5	5553 84	5554 84	2 P + ⊥
5	5553 85	5554 85	3 P + ⊥
5	5553 86	5554 86	3 P + N + ⊥
			380/415 V~
5	5553 88	5554 88	3 P + ⊥
5	5553 89	5554 89	3 P + N + ⊥
			Mobile sockets
			Supplied unlocked
5	16 A 5553 01	32 A —	100/130 V~ 2 P + ⊥
			200/250 V~
5	5553 04	5554 14	2 P + ⊥
5	5553 05	5554 15	3 P + ⊥
5	5553 06	5554 16	3 P + N + ⊥
			380/415 V~
5	5553 08	5554 18	3 P + ⊥
5	5553 09	5554 19	3 P + N + ⊥
			Straight plugs
			Supplied unlocked
5	16 A 5553 21	32 A 5554 31	100/130 V~ 2 P + ⊥
			200/250 V~
5	5553 24	5554 34	2 P + ⊥
5	5553 25	5554 35	3 P + ⊥
5	5553 26	5554 36	3 P + N + ⊥
			380/415 V~
5	5553 28	5554 38	3 P + ⊥
5	5553 29	5554 39	3 P + N + ⊥
			Appliance inlets
5	16 A 0568 03	32 A 0568 23	200/250 V~ 2 P + ⊥
			380/415 V~
5	0568 07	0568 27	3 P + ⊥
5	0568 08	0568 28	3 P + N + ⊥

P 17 Tempra Pro IP 66/67/69¹ - LV 63 and 125 A

sockets, plugs, mobile sockets and appliance inlets and IP 66/67/69¹ LV 32 A for refrigerated containers



5555 59



5555 09



6571 06

Technical characteristics p. 20

Pack	Cat. Nos.		Surface mounting sockets
	63 A	125 A	200/250 V~
2	5555 54	—	2 P + ⊥
2	5555 55	—	3 P + ⊥
2	5555 56	—	3 P + N + ⊥
			380/415 V~
2 1	5555 58	5556 58	3 P + ⊥
2 1	5555 59	5556 59	3 P + N + ⊥
			Panel mounting sockets inclined outlet
			Can be fixed on faceplates Cat. No. 0577 17 (p. 18)
2	63 A 5555 84	125 A —	200/250 V~ 2 P + ⊥
2	5555 85	—	3 P + ⊥
2	5555 86	—	3 P + N + ⊥
			380/415 V~
2 1	5555 88	5556 88	3 P + ⊥
2 1	5555 89	5556 89	3 P + N + ⊥
			Mobile sockets
			200/250 V~
2	63 A 5555 04	125 A —	2 P + ⊥
2	5555 05	—	3 P + ⊥
2	5555 06	—	3 P + N + ⊥
			380/415 V~
2 1	5555 08	5556 08	3 P + ⊥
2 1	5555 09	5556 09	3 P + N + ⊥
			Straight plugs
			200/250 V~
2	63 A 5555 24	125 A —	2 P + ⊥
2	5555 25	—	3 P + ⊥
2	5555 26	—	3 P + N + ⊥
			380/415 V~
2 1	5555 28	5556 28	3 P + ⊥
2 1	5555 29	5556 29	3 P + N + ⊥
			Appliance inlets
2	63 A 5555 14	125 A —	200/250 V~ 2 P + ⊥
			380/415 V~
2 1	5555 18	5556 18	3 P + ⊥
2 1	5555 19	5556 19	3 P + N + ⊥
			Combined unit, plug and mobile socket for refrigerated containers
1	32 A 6571 06		32 A - 440 V~ - 50/60 Hz - 3 P + ⊥ - 3 hours IK 09 Plastic body and cover Stainless steel screws Combined unit with interlocked switched socket. Double mechanical interlock Cable glands are not supplied Panel mounting socket inclined outlet Mobile socket With cable grip Ø12 to 21.5 mm Straight plug With cable grip Ø12 to 21.5 mm
5	5554 91		
5	5554 21		
5	5554 41		

1: IP69 available in 63 and 125 A in mobile sockets and straight plugs only