


EZ-Path® fire rated pathway Series 44+

selection chart

CE marked certification

Fire resistance : EN 1366-3 Classification : EN 13501-2
ETA 18 / 0412

All EZ-Path systems are approved empty up to 100 % visual fill of cable



CM250058 (EZD44T)

Cat. Nos.		Plate kit	Plate dim. (mm) (w x h)	EZ-Path systems	Opening dim. (mm) (w x h or Ø)	Ø cables (mm)
1 x CM250058 + CM250250 (1 x EZD44T+ EZP544WT)	1 x		610 x 272		105 x 120	OD ≤ Ø 80
2 x CM250058 + CM250250 (2 x EZD44T+ EZP544WT)	2 x				206 x 120	
3 x CM250058 + CM250250 (3 x EZD44T+ EZP544WT)	3 x				309 x 120	
4 x CM250058 + CM250250 (4 x EZD44T+ EZP544WT)	4 x				412 x 120	
5 x CM250058 + CM250250 (5 x EZD44T+ EZP544WT)	5 x				515 x 120	
1 x CM250058 + CM350703 (1 x EZD44T+ EZP144MBE)	1 x		56 mm bracket width		Ø 152 - Ø 155	OD ≤ Ø 21
1 x CM250058 + CM250260 (1 x EZD44T + EZG144T)	1 x		274 x 264		Ø 152	OD ≤ Ø 21 OD ≤ Ø 50 OD ≤ Ø 80
2 x CM250058 + CM350704 (2 x EZD44T + EZP544MBE)	2 x		56 mm bracket width		216 x 144 (+/- 8 mm) max. 224 x 152	OD ≤ Ø 21
3 x CM250058 + CM350704 (3 x EZD44T + EZP544MBE)	3 x				330 x 144 (+/- 8 mm) max. 338 x 152	
4 x CM250058 + CM350704 (4 x EZD44T + EZP544MBE)	4 x				440 x 144 (+/- 8 mm) max. 448 x 152	
5 x CM250058 + CM350704 (5 x EZD44T + EZP544MBE)	5 x				542 x 144 (+/- 8 mm) max. 550 x 152	
1 up to 5 x CM250058 + CM350704 (1 up to 5 x EZD44T + EZP544MBE) Rockwool FirePro® Ablative Coated Batt and FirePro® Compound	1 up to 5 x	 50 mm thick FirePro® Ablative coated batt Rockwool FirePro® Firestop compound	56 mm bracket width		max. 550 x 320	OD ≤ Ø 21
4 x CM250058 + CM250370 (4 x EZD44T + EZG444T)	4 x		568 x 210		445 x 155	OD ≤ Ø 80