

Panels.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

Low glare for visual comfort

Each panel is compatible with our three hour non-maintained emergency pack

Installation is quick and easy

Various sizes available



Available in both TP(a) and TP (b) to suit your preference

Suitable for reading, writing, meetings and computer-based work

Supplied with 1m long safety steel cable

Glow wire test:
P2 panels - 650°C
P3 panels - 850°C

Beam angle: 90° 110°



Solis 1200X600

1200 x 600 LED panel

FEATURES

Wattage	60W
IP rating	IP40
IK rating	IK06
UGR	<19 22
Sensor	No
Dimmable	DALI 2 1-10V
Input	220-240V
LED lifetime	50,000h
SDCM	6SDCM
Flicker free	Yes
Emergency version available	Yes, using CWD LEDEP09 (sold separately)

INSTALLATION INFORMATION

Install connector type	Integrated terminals
Insulation coverable	(Yes, contact us at 01604 495 151)
Inrush current	50A, 0.05ms
Construction material	PS(P2) / PC(P3) Aluminium Painted steel
Weight	UGR19: 4500g UGR22: 4300g
Maximum ambient temperature	40°
SELV	Yes
Building regulations	Part P & L
Electric class (1, 2, 3)	2

PHOTOMETRICS @ 25°C

Product code	Wattage	Dimming	UGR	Colour	Beam angle	CRI	lm	lm/W
P3C19S60W	60W	Non-Dim	UGR19 TP(a)	4000K	90°	>80Ra	6600	110
P3C19D60W	60W	DALI 2	UGR19 TP(a)	4000K	90°	>80Ra	6600	110
P3C19V60W	60W	1-10V	UGR19 TP(a)	4000K	90°	>80Ra	6600	110
P2C22S60W	60W	Non-Dim	UGR22 TP(b)	4000K	110°	>80Ra	6600	110
P2C22D60W	60W	DALI 2	UGR22 TP(b)	4000K	110°	>80Ra	6600	110
P2C22V60W	60W	1-10V	UGR22 TP(b)	4000K	110°	>80Ra	6600	110

WIRING INFORMATION

Cable / flying lead	0.75-1.5mm²
Type of wiring required	Parallel

ACCESSORIES

LEDEP09	3hr non-maintained emergency pack	Sold separately	315
P1SKC	Suspension kit for 1200 x 600 Panels.	Sold separately	307
P2SMC	Surface mount kit for 1200 x 600 LED panel	Sold separately	307