

Anti-corrosives.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

Robust fixture made of polycarbonate base and translucent polycarbonate diffuser

Held together with anti-tamper stainless steel clips allowing the removal of the diffuser during installation

Tough exterior provides an IP65 and IK08 housing protecting the LED components inside


Compression cable glands allowing the entry/exit of wires without compromising water tightness of the fixture

Mounting brackets included

Available with microwave sensor for further energy savings

Loop-in loop-out terminals

Beam angle: 125x105°



Caiman 5ft 28-29W

5ft Single, anti-corrosive LED

FEATURES

Wattage	28 - 29W
IP rating	IP65
IK rating	IK08
Colour flexibility	Fixed colour
UGR	20
Dimmable	DALI option
Input	220-240V
LED lifetime	50,000h L70 B10
SDCM	5SDCM
Emergency version available	Yes

INSTALLATION INFORMATION

Install connector type	Loop-in loop-out
Inrush current	11A, 150µs DALI : 26A, 160µs
Construction material	PC Stainless Steel
Weight	1713g
Maximum ambient temperature	40°C
SELV	Yes
Building regulations	Part P
Electric class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Wattage	Feature	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
AC5SS40	28W	Standard	4000K	125x105°	80Ra	4000	143	1135
AC5SM40	29W	Microwave sensor	4000K	125x105°	80Ra	4000	143	1135
AC5SD40	28W	DALI dimmable	4000K	125x105°	80Ra	4000	143	1135
AC5SS40EM	28W	Emergency	4000K	125x105°	80Ra	4000	143	1135
AC5SM40EM	29W	Emergency Microwave sensor	4000K	125x105°	80Ra	4000	143	1135
AC5SD40EM	28W	Emergency DALI dimmable	4000K	125x105°	80Ra	4000	143	1135

WIRING INFORMATION

Cable required for connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm²
Type of wiring required	Parallel

ACCESSORIES

JB3	Waterproof junction box	Sold separately	422
-----	-------------------------	-----------------	---------------------