

Anti-corrosives.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

Robust fixture made of polycarbonate base and translucent polycarbonate diffuser

Held together with anti-tamper stainless steel clips allowing the removal of the diffuser during installation

Tough exterior provides an IP65 and IK08 housing protecting the LED components inside


Compression cable glands allowing the entry/exit of wires without compromising water tightness of the fixture

Mounting brackets included

Available with microwave sensor for further energy savings

Loop-in loop-out terminals

Beam angle: 125x105°



Caiman 6ft 36-37W

6ft Single, anti-corrosive LED

FEATURES

Wattage	36 - 37W
IP rating	IP65
IK rating	IK08
Colour flexibility	Fixed colour
UGR	20
Dimmable	DALI option
Input	220-240V
LED lifetime	50,000h L70 B10
SDCM	5SDCM
Emergency version available	Yes

INSTALLATION INFORMATION

Install connector type	Loop-in loop-out
Inrush current	11A, 150µs DALI : 23A, 200µs
Construction material	PC Stainless Steel
Weight	1945g
Maximum ambient temperature	40°C
SELV	Yes
Building regulations	Part P
Electric class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Wattage	Feature	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
AC6SS40	36W	Standard	4000K	125x105°	80Ra	5100	141	1343
AC6SM40	37W	Microwave sensor	4000K	125x105°	80Ra	5100	138	1343
AC6SD40	36W	DALI dimmable	4000K	125x105°	80Ra	5100	141	1343
AC6SS40EM	36W	Emergency	4000K	125x105°	80Ra	5100	141	1343
AC6SM40EM	36.5W	Emergency Microwave sensor	4000K	125x105°	80Ra	5100	140	1343
AC6SD40EM	36.5W	Emergency DALI dimmable	4000K	125x105°	80Ra	5100	140	1343

WIRING INFORMATION

Cable required for connector	H05RN-F cable diameter 4 - 10mm, max conductor size 3x 1.5mm²
Type of wiring required	Parallel

ACCESSORIES

JB3	Waterproof junction box	Sold separately	422
-----	-------------------------	-----------------	---------------------