



HIGH BAY SPECIFICATION SHEET




COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

 @collingwoodLED

 /collingwoodlighting

 collingwoodled

Springbok

Microwave sensor to save energy and cost

FEATURES

IP rating	IP65
Sensor	Microwave
Dimmable	Yes
Input	Mains AC

INSTALLATION INFORMATION

Install Connector Type	Flying lead
Construction Material	Plastic
Weight	0.20Kg
Maximum ambient temperature	70°C
Electric Class (1, 2, 3)	1

WIRING INFORMATION

Cable / Flying Lead	800mm E475602 5 Core Ø8mm
Type of Wiring Required	Parallel

ACCESSORIES

HBASDHSRC	Remote controller to set up HBASDHS & LBASDHS sensors	Sold Separately
-----------	---	-----------------

PRODUCT CODES

Product code	Finish	Description	Wattage
HBAS	White	Microwave sensor	200W
HBASDHS	Black	Microwave & Daylight Harvesting Sensor	
HBASDHSRC	White	Microwave & Daylight Harvesting Sensor Controller	

GUARANTEE / WARRANTY

5 year extended guarantee

FEATURES & BENEFITS

IP65 rated meaning it can be used in conditions where it may be wet

Mounting height up to 15m

Achieves step dimming

Provides energy savings

Lighting will only turn on when it detects movement

Ideal for aisle lighting

Customise the dipswitches according to preference for more energy cost savings

Change the detection area on where movement is detected, along with hold time where the time period of light remains on at 100% brightness, if no further movement is detected

Stand by time can be changed, this is the time period the light remains on at pre-set dimming level once the hold time is finished

Customised the dimming level and enable/disable the daylight sensor

