



Salvus Emergency Exit Box

47lm, emergency exit box

FEATURES

IK rating	IK08
IP rating	IP20
Colour flexibility	Fixed
Input	220-240V
CRI	>80Ra

INSTALLATION INFORMATION

Install Connector Type	Push-fit Connector
Inrush Current	12A 56µs
Construction Material	Lens PC Housing PC
Weight	0.6Kg
Maximum ambient temperature	45°C
Electric Class (1, 2, 3)	2

PHOTOMETRICS @ 25°C

Product code	Feature I	Feature II	Feature III	Wattage	Colour	lm
EMBX35M	Maintained & Non-Maintained	View Dist 35m	Manual Test NiCd	3.5W	6500K	47 lm
EMBX35S	Maintained	View Dist 35m	Self Test LiFePO4	3.5W	6500K	47 lm

ACCESSORIES

EMBXUP	Pictogram Arrow UP.	Sold Separately
EMBXDO	Pictogram Arrow DOWN.	Sold Separately
EMBXRI	Pictogram Arrow RIGHT.	Sold Separately
EMBXLE	Pictogram Arrow LEFT.	Sold Separately



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

2 Year Extended Warranty Manual Test, 3
Year Extended Warranty Self Test

FEATURES & BENEFITS

Terminals allow for both maintained and non-maintained usage, by simply connecting the cables to the push-fit terminals

Manual test (without button) or self test versions available

NiCd, has proven technology which is widely used


Lithium batteries are long-lasting and have a long-life

Housing is rugged and made from Polycarbonate


35m viewing distance allowing it to be assembled in many different room dimensions

Complying with ISO 3864-1, and proud members of the ICEL

390.3mm



195.3mm



30mm