



Salvus Emergency Exit Blade

50lm, emergency exit blade

FEATURES

IK rating	IK08
IP rating	IP20
Colour flexibility	Fixed
Input	220-240V
CRI	>80Ra

INSTALLATION INFORMATION

Install Connector Type	Push-fit Connector
Inrush Current	10.3A 100µs
Construction Material	Lens PC Housing PC
Weight	0.9Kg
Maximum ambient temperature	45°C
Electric Class (1, 2, 3)	2

PHOTOMETRICS @ 25°C

Product code	Feature I	Feature II	Feature III	Wattage	Colour	lm
EMBL30M	Maintained	View Dist 30m	Manual Test LiFeP04	4.0W	6500K	50 lm
EMBL30S	Maintained	View Dist 30m	Self Test LiFeP04	4.0W	6500K	50 lm

ACCESSORIES

EMBLUP	Pictogram Arrow UP.	Sold Separately
EMBLDO	Pictogram Arrow DOWN.	Sold Separately
EMBLRI	Pictogram Arrow RIGHT.	Sold Separately
EMBLLE	Pictogram Arrow LEFT.	Sold Separately
EMBLSK	Suspension Kit (2x 1m cable + fixings)	Sold Separately



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

3 Year Extended Warranty

FEATURES & BENEFITS

Maintained, so it can be turned on/off when the mains is on

Manual test or self test versions available

Lithium batteries are long-lasting and have a long-life

Has three M20 entry knock-outs (one on each side and one in the bottom), and rear BESA box fixing points, so can fit to most installation methods

Housing is rugged and made from Polycarbonate

30m viewing distance allowing it to be assembled in many different room dimensions

Complying with ISO 3864-1, and proud members of the ICEL

