
VDE RANGE





VDE FULLY INSULATED COMBINATION PLIERS

Manufactured to DIN ISO 5746 Specifications. Tested to EN 60900 Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from special tool steel, oil hardened and tempered. Smoothly ground chrome plated heads with cutting edges separately induction hardened to 60HRC for cutting medium-hard and hard wire. Heavy two colour insulated handles with slip guards for extra comfort and safety. Display packed.

		Cuttin	g Capacities-mn	n	
Stock Overall No. Length	Cable dia.	Cable mm ²	Med/Hard Wire dia.	Hard Wire dia.	
81204 180mm 81212 200mm	12.0 13.0	16.0 16.0	3.4 3.8	2.2 2.5	

High leverage joint =



VDE FULLY INSULATED HIGH LEVERAGE COMBINATION PLIERS

Manufactured to DIN ISO 5746 Specifications. Tested to EN 60900 Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from special tool steel, oil hardened and tempered. Smoothly ground chrome plated heads with cutting edges separately induction hardened to 64HRC for cutting hard and piano wire. Heavy two colour insulated handles with slip guards for extra comfort and safety. Display packed.

	-		-		
Stock Overall	Cable	Cable	Capacities-mi Hard	Piano Wire	
No. Length	dia.	mm ²	Wire dia.	dia.	
49168 180mm	11.5	16.0	2.5	2.0	
59818 200mm	13.0	25.0	2.8	2.2	
49169 225mm	14.0	25.0	3.0	2.5	



3 13 86 200SBE **VDE ELECTRICIANS UNIVERSAL INSTALLATION PLIERS**

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900. Professional Quality, for the all-round professional, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Multifunctional electrical installation pliers ideal for gripping flat and round material, bending, deburring, cutting cable, stripping and crimping ferrules; 6 functions in one pair of pliers! Built in shears allow up to 15mm diameter copper cable to be cut. Manufactured from high-grade oil hardened steel with chrome plated head and precision ground stripping holes. Separately induction hardened cutting edges give a clean cut every time. Heavy duty insulated handles and slip guards for extra comfort and safety.

Stock No.	Overall Length	Stripping Cap. mmØ	Crimp Cable Links mm ²	Cutting Cable mmØ	
31460	200mm	0.75-2.5mm	0.5-2.5mm	15mm	



4 25 06 VDE FULLY INSULATED LONG NOSE PLIERS

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900 Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from special tool steel, oil hardened and tempered. Smoothly ground chrome plated head with cutting edges separately induction hardened to 60HRC for cutting soft wire 2.5mm and medium wire 1.6mm. Flat-round jaws have serrated gripping surfaces. Heavy two colour insulated handles with slip guards for extra comfort and safety. Display packed.

		Jaw Size						
Stock	Overall	Length	W-	mm	Thick	ness-mm		
No.	Length	· · ·	Base	Tip	Base	Tip		
81238	160mm	50.0mm	16.5	3.0	9.0	2.5		



VDE FULLY INSULATED LONG NOSE PLIERS

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900 Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from vanadium steel, oil hardened and tempered. Smoothly ground chrome plated head with cutting edges separately induction hardened to 61HRC for cutting medium-hard wire 3.2mm and hard wire 2.2mm. Straight, long flat-round jaws are serrated for easy grip. Heavy two colour insulated handles with slip guards for extra safety. Display packed.

			Jaw Size					
Stock	Overall	Length	W-	mm	Thickr	iess-mm		
No.	Length	-	Base	Tip	Base	Tip		
81246	200mm	73.0mm	17.5	3.0	9.5	2.5		



6 26 26 200SB FULLY INSULATED ANGLED LONG NOSE PLIERS

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900 Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Manufactured from vanadium steel, oil hardened and tempered. Smoothly ground cutting edges separately induction hardened to 61HRC for cutting medium 3.2mm and hard wire 2.2mm. Straight, half round jaws have serrated gripping surfaces. Heavy insulated handles with slip guards for extra comfort and safety.

			Jaw Size						
Stock	Overall	Length	W-	mm	Thick	ness-mm			
No.	Length	· · ·	Base	Tip	Base	Tip			
34056	200mm	73.0mm	17.5	3.0	9.5	2.5			



DISMANTLING PLIERS

Manufactured to DIN ISO 5745 Specifications. Tested to EN 60900 Professional Quality, tested to 10,000V and insulated to 1000V AC and 1500V DC for live line working. Thanks to its circular cutting edge they enable easier access into deep mounted junction boxes, easily stripping cables without damage. Universally useful, the precision 1.5 and 2.5 mm² wire stripping holes and diagonal cutters used for conductors, wires, small screws and nails. All cutting edges are additionally induction hardened for a longer life. Manufactured from oil-hardened chrome vanadium steel. Perfect for dismantling and stripping round sheathed and damp-proof installation cables.

Stock No.	Overall Length	Stripping Capacity mmØ	Cable Stripping mmØ		
14738	165mm	1.5-2.5mm	8-13mm		