




Range of Watertight surface-mounting boards made in polyester material reinforced with fibreglass. In compliance with IEC 61439-1 (CEI 17/113), IEC 61439-2 (CEI 17/114), IEC 60670-1 (CEI 23/48), IEC 60670-24 (CEI 23/49) e IEC 62208 (CEI 17-87). Available in 7 sizes, transparent and black door versions with IP66 protection degree. Fast&Easy accessories, made in metal, allow the installation of modular devices and moulded-case circuit breakers up to 250A into the boards, reducing assembly times by up to 40%. Indicated for automation and distribution for indoor and outdoor applications.

|                                   |                                                           |                                       |                                                          |
|-----------------------------------|-----------------------------------------------------------|---------------------------------------|----------------------------------------------------------|
| Glow Wire Test                    | 960 °C                                                    | Insulation voltage                    | 1000 V                                                   |
| Standard                          | EN 61439-1, EN 61439-2, EN62208, EN 60670-1, IEC 60670-24 | Surface-mounting brackets             | GW46446-GW46451                                          |
| Kit for double insulation restore | GW46526                                                   | Thermo-pressure with ball             | 200 °C                                                   |
| Nominal dim. LxHxD (mm)           | 585x800x300                                               | Insulation voltage                    | 1000 V according to EN 62208 both in ac as well as in dc |
| Family                            | 46 QP                                                     | Maximum rated insulation voltage (Ui) | 690 V                                                    |
| No. locks                         | 2                                                         | Dispersible power A (W)               | 205                                                      |
| Dispersible power B (W)           | 146                                                       | Insulation class                      | II                                                       |
| IP degree                         | IP66                                                      | Shock resistance                      | IK10                                                     |
| Functional dim. LxHxD (mm)        | 591x804x300                                               | Operating temperature                 | -25 +60 °C                                               |
| Type of material                  | Halogen-free in compliance with EN 60754-2                | Electrocod                            | 0321                                                     |
| Type of door                      | Blank door                                                | Colour                                | Grey RAL 7035                                            |
| Characteristics                   | UV resistance (EN 62208)                                  | Material                              | Polyester reinforced with fibreglass                     |
| No. of modules EN 50022           | 140 (28x5)                                                |                                       |                                                          |

#### BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

| Saline solution | Acids              |                    | Bases              |                    | Solvents           |                    |               |                    | Mineral oil | UV rays   |
|-----------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|---------------|--------------------|-------------|-----------|
|                 | Concentrated       | Diluted            | Concentrated       | Diluted            | Hexane             | Benzol             | Acetone       | Ethyl alcohol      |             |           |
| Resistant       | Limited resistance | Limited resistance | Limited resistance | Limited resistance | Limited resistance | Limited resistance | Not resistant | Limited resistance | Resistant   | Resistant |

#### DIMENSIONAL



#### TECHNICAL SYMBOLOGY

**GWT**

960 °C



1000 V according to EN 62208 both in ac as well as in dc



II



-25 +60 °C



Halogen-free in compliance with EN 60754-2



UV resistance (EN 62208)

#### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 06/02/2019

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice