

**SAK Series, Accessories  
Q 2 AKZ4**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergsstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



This type of cross-connection has a pre-assembled captive cross-connection lug, cross-connection sleeve and fixing screw.

All the individual parts are available separately on request. During installation, the pre-assembled cross-connectors are simply placed in the cross-connection slot in the middle of the terminal and screwed tight.

**General ordering data**

Type	Q 2 AKZ4
Order No.	<a href="#">0336400000</a>
Version	SAK Series, Accessories, Cross-connector, for cross-connection link, No. of poles: 2
GTIN (EAN)	4008190037680
Qty.	50 pc(s).

**SAK Series, Accessories  
Q 2 AKZ4**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergsstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data****Dimensions and weights**

Length	4 mm	Width	11.1 mm
Height	9.9 mm	Net weight	1.48 g

**Temperatures**

Operating temperature	Storage temperature
-----------------------	---------------------

**Additional technical data**

Explosion-tested version	No	Installation advice	Direct mounting
Version	for cross-connection link		

**Rated data**

Rated current	24 A
---------------	------

**Material data**

Material	Cu Zn	Colour	Grey
----------	-------	--------	------

**System specifications**

Product family	SAK Series, Accessories
----------------	-------------------------

**Classifications**

ETIM 2.0	EC000489	ETIM 3.0	EC000489
UNSPSC	30-21-18-01	eClass 4.1	27-14-11-99
eClass 5.1	27-14-11-40	eClass 6.2	27-14-11-40
eClass 7.1	27-14-11-40		

**Product information**

Descriptive text technical data      Rated current is 32 A for all cross-connections when used in DK 4/DK4Q and QV versions.

Descriptive text accessories      Q2-Q10 AKZ 4, can also be used for all DK 4/DK4Q and DK4QV versions.

**Approvals**

Approvals	
ROHS	Conform