

Products with extended versions and special devices – 7 pole

to DIN VDE 0623-1, EN 60309-1. Colour: electric grey and/or colour code.  Highly resistant to chemicals. Other voltages and frequencies available on request. For drawings and dimensions see page 105 - 117.



Wall mounted receptacle
with highly heat resistant contact carrier, nickel plated contacts, internal fixing, enclosure base can be turned 180°

IP 44

Std. Pack. Qty: 10

Drawing: 1 MB 43/257

A	P	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz
16	7	733	734	1035
32	7	735	736	1040



<



Wall mounted receptacle

switched, mechanical DUO-interlock, highly heat resistant contact carrier, nickel plated contacts, 6 pole switch with 2 auxiliary contacts (1 NO and 1 NC), receptacles can be padlocked

IP 67

Std. Pack. Qty: 1

Drawing: 1 MB 382

A	P	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz
with 6 pole switch:				
16	7		7306	
32	7		7307	
with 3 pole switch:				
16	7		5785	
32	7		6106	



<



Panel mounted receptacle
highly heat resistant contact carrier,
nickel plated contacts,
20° inclination

IP 67
Std. Pack. Qty: 10
Drawing: 1 MB 251

A	P	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz
16	7	2883	2459	2296
32	7	3775	2317	2212

	Plug AM-TOP				
	highly heat resistant contact carrier, nickel plated contacts, single part body, cable gland and sealing, strain relief and protection against kinking				
	IP 44				
	Std. Pack. Qty: 10				
	A	P	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz
	16	7	741	742	1055
	32	7	743	744	1060