

Receptacle combinations – DELTA-BOXES and receptacle strips

Pre-wired for installation, IP 44¹⁾ / 67 ¹⁾ Regarding portable receptacle combinations in IP 44 please see page 106 for further information.
With cable grip and installed hanging hook. Other combinations on request. Dimensions page 115.

			
Fitted with 3 CEE 16 A, 5 p, 400 V	Fitted with 3 CEE 32 A, 5 p, 400 V	Fitted with 1 CEE 16 A, 5 p, 400 V 3 SCHUKO® 16 A, 230 V	Fitted with 2 CEE 16 A, 5 p, 400 V 1 CEE 16 A, 3 p, 230 V
Fusing	Fusing	Fusing	Fusing
Connection For 1 cable up to 5 x 10 mm ²	Connection For 1 cable up to 5 x 10 mm ²	Connection For 1 cable up to 5 x 10 mm ²	Connection For 1 cable up to 5 x 10 mm ²
Connection and load values	Connection and load values	Connection and load values	Connection and load values
Protection type IP 44	Protection type IP 44	Protection type IP 44	Protection type IP 67
Part no. 92917	Part no. 90839	Part no. 92658	Part no. 92893
			
Fitted with 3 CEE 16 A, 3 p, 110 V	Fitted with 3 CEE 16 A, 3 p, 230 V	Fitted with 3 CEE 16 A, 5 p, 400 V	Fitted with 2 CEE 16 A, 5 p, 400 V 1 SCHUKO® 16 A, 230 V
Fusing	Fusing	Fusing	Fusing
Connection For 1 cable up to 3 x 10 mm ²	Connection For 1 cable up to 3 x 10 mm ²	Connection For 1 cable up to 5 x 10 mm ²	Connection For 1 cable up to 5 x 10 mm ²
Connection and load values	Connection and load values	Connection and load values	Connection and load values
Protection type IP 44	Protection type IP 44	Protection type IP 44	Protection type IP 44
Part no. 96227	Part no. 96489	Part no. 96705	Part no. 96703