



1 265KA

RIVETER WITH RIVETS

DIY users riveter with blue enamelled pressed steel frame, chrome molybdenum steel jaws and moulded grip handles. Supplied with four nozzles to accept 2.4, 3.2, 4.0 and 4.8mm aluminium alloy blind rivets, plus an assortment of approximately 60 rivets. Display packed.

Stock No.	Description
27847	Riveter Kit
28878	Spare Jaws



2 268AKA

TWO WAY RIVETER KIT

General duty riveter with head that will operate at 90° or 180°. Chrome molybdenum jaws with four nozzles to accept 2.4, 3.2, 4.0 and 4.8mm aluminium alloy blind rivets. Supplied with approximately 60 assorted rivets, nozzle wrench and plastic carrying case. Display packed.

Stock No.	Description
27848	Riveter Kit
28879	Spare Jaws



3 264KA

RIVETER KIT

DIY users riveter with cast aluminium body and carbon steel moving handle with moulded grips. Supplied with nozzle wrench for use with the four interchangeable nozzles, which accept 2.4, 3.2, 4.0 and 4.8mm alloy and blind rivets plus an assortment of approximately 100 rivets. Display packed.

Stock No.	Description
27843	Riveter Kit
28879	Spare Jaws



4 4417

HEAVY DUTY AIR RIVETER

Designed for ease of use and durability this riveter is ideal for heavy or light production requirements. Its quiet operation and speed of use adds value with a cost effective performance. Suitable for aluminium alloy rivets only. Display carton. Specification:

Capacity	... 2.4, 3.2, 4.0, 4.8 and 6.3mm
Traction power	... 1890kg
Operating air pressure	... 60-100psi (4.1-7.0bar)
Average air consumption	... 4.0cfm (114L/min)
Hose size	... 3/8" I.D
Air Inlet	... 1/4" BSP
Weight (riveter only)	... 2kg

Stock No.
61429



5 4296K

AIR RIVETER KIT

Designed for ease of use and durability this kit satisfies light production needs. Its quiet operation and speed of use adds value with a cost effective performance.

Supplied complete in carrying case. Suitable for aluminium alloy rivets only. Display carton. Contents:

- riveting gun • 4 nozzles: 2.4, 3.2, 4.0 and 4.8mm
- spare jaw set • rubber exhaust tailpipe • two spanners
- 5mm hexagon key • swivel connector with 1/4" BSP thread • oil pot. Specification:

Capacity	... 2.4, 3.2, 4.0 and 4.8mm
Traction power	... 998kg
Operating air pressure	... 60-90psi (4.1-6.2bar)
Average air consumption	... 4.2cfm (119L/min)
Hose size	... 3/8" I.D
Air Inlet	... 1/4" BSP
Weight (riveter only)	... 1.6kg

Stock No.
33746



6 RIV

BLIND RIVETS

Aluminium rivets with steel mandrel. Average contents 50 rivets per card. Display packed.

Stock No.	Rivet Dia.	Drill Size	Head Length
13554	2.4mm	2.5mm	7.0mm
14007	3.2mm	3.3mm	5.2mm
13555	3.2mm	3.3mm	10.8mm
14008	3.2mm	3.3mm	15.8mm
13556	4.0mm	4.1mm	5.6mm
14009	4.0mm	4.1mm	10.0mm
14010	4.0mm	4.1mm	15.8mm
13557	4.8mm	4.9mm	10.0mm
14011	4.8mm	4.9mm	10.0mm
14012	4.8mm	4.9mm	16.0mm




7 RIV/TUB

TUBS OF BLIND RIVETS

Aluminium rivets with steel mandrel. 3.2mm rivets in tubs of approx. 2000. 4.0mm rivets in tubs of approx. 1200. 4.8mm rivets in tubs of approx. 800.

Stock No.	Rivet Dia.	Drill Size	Head Length
37657	3.2mm	3.3mm	10.2mm
37658	4.0mm	4.1mm	10.2mm
37659	4.8mm	4.9mm	10.2mm



8 RIV/W

BACKING WASHERS

For use with rivets listed under Blind Rivets. Used on back of blind rivets for extra fixing security. Average contents 100 washers per card. Display packed.

Stock No.	for Rivet Diameter	Diameter I/D x O/D
14013	2.4mm	2.6 x 7.8mm
14014	3.2mm	3.3 x 7.8mm
14015	4.0mm	4.2 x 9.8mm
14016	4.8mm	5.2 x 9.8mm

PRODUCT INFORMATION

IMPORTANT NOTE: Jaw sets will wear during use. They should be replaced if grip fails.

