



NEW 1/4" BSP

1 RAH12

12M RETRACTABLE AIR HOSE REEL

10mm PVC air hose, providing 10/24 bar working/burst pressure. The 6.5 x 10mm thick airline, on a ratchet lock system is 'stoppable' every 20cm (approx) and is attached to a 180° ceiling/wall mounting bracket. Supplied with 1/4 BSP threaded connectors.

Specification:

Hose length	... 12M
Hose size	... 6.5 x 10mm
Hose connection	... 1/4 BSP thread
Operating temperature	... -5 to 45°C

Stock No.	Price each
15047	



NEW 1/4" BSP 3/8" BSP

2 RAH

RETRACTABLE AIR HOSE REELS

3/8" PVC hybrid air hose, providing 18/54 bar working/burst pressure. The 8 x 12mm thick airline stops in any position and is attached to a 180° ceiling/wall mounting bracket and the slow return mechanism delivers excellent user safety. Fitted with an internal rewind guide prevents hose tangling. Supplied with 1/4 BSP threaded connectors.

Specification:

Hose length	... 10M
Hose size	... 8 x 12mm
Hose connection	... 1/4 BSP thread
Max. working/burst pressure	... 1.8/5.4MPa (261/783psi)

Operating temperature ... -5 to 45°C

Stock No.	Length	Price each
15048	10M	
15049	30M	



NEW 3/8" BSP

3 RAH15

15M RETRACTABLE AIR HOSE REEL

Expert Quality, 3/8" rubber air hose, the latching mechanism provides 20 bar max operating pressure. The airline stops in any position and the reel can be solidly mounted to a ceiling/wall or vehicle. (note: does not have 180° bracket).

Specification:

Hose connection	... 1/4 BSP thread
Operating temperature	... -5 to 45°C

Stock No.	Length	Price each
15050	15M	

1/4" BSP 3/8" BSP



4

7.6M NYLON RECOIL AIR HOSES

DIY recoil type air hose which allows good access to working areas. Supplied with spring protection guards and male brass end fittings, one 360° swivel the other fixed. Display packed.

Stock No.	Part No.	Hose Connections	Price each
52662	4225/1A	1/4" BSP male	
52663	4225/2A	3/8" BSP male	

1/4" BSP 3/8" BSP



5

11.5M HEAVY DUTY NYLON RECOIL AIR HOSES

Hoses manufactured to BS5409 Specifications

Recoil type air hose which allows good access to working areas. For the workshop and industrial user. Supplied with spring protection guards and 360° swivel end male fittings. Maximum working pressure at 20°C; - 1.4MPa (203psi). Display packed.

Stock No.	Part No.	Hose Connection	Price each
76981	4282C	1/4" BSP male	
76982	4283C	3/8" BSP male	

1/4" BSP 3/8" BSP 1/2" BSP



6 4311

600mm WHIP HOSES

Manufactured to BS Specifications

Health and Safety Executive guidance regulations recommend a flexible isolating hose to be used between the air tool and coupling, thus isolating the tool's vibration. Supplied with PCL adaptor and appropriate male tailpiece. Display packed.

Stock No.	Part No.	Male Thread	Hose I/D x O/D	Price each
54438	4311	1/4" BSP	7 x 14mm	
54439	4312	3/8" BSP	10 x 17mm	
54440	4313	1/2" BSP	13 x 21mm	

1/4" BSP



7 CONNECT KIT

1/4" STANDARD AIR TOOL CONNECTION KIT

Air tool connection kit consisting of high pressure PVC hose, PCL coupling set and female coupling. Sold loose.

Contents:

- Air line hose, 15.2M x 1/4" bore, Stock No. 36939
- Air line coupling set, 1/4 BSP, Stock No. 37844
- 1/4" Parallel female coupling, Stock No. 37827

Stock No.	Price per kit
64503	