

1 PLF POST LEVEL

NEW



Rigid post level made from durable reinforced ABS plastic. Designed to plumb pipes, posts, level RSJ's and other applications where vertical or horizontal is required. Attached with four magnetic pads for working with steel posts and fitted with a strong elastic band for fixing to non-magnetic surfaces. Two horizontal and one plumb tubular acrylic vials for convenience with an accuracy of 0.1deg (1.75mm/M). Dimensions level 121 x 78mm. Display packed.

Stock
No.
75042

NEW

2 LDM-40M 40M DISTANCE MEASURER

Measures distances up to 40M/132ft in metric or imperial. The backlight LED screen displays area, volume and indirect measurements with an accuracy of ± 1.5 mm. The memory function enables addition, multiplications and subtractions. Uses 2 x AAA batteries (not supplied). Display packed.



Stock No.	Description
15102	Distance Measurer
61833	Batteries (4 x AAA)

CLASS 2 LASER PRODUCT



3 LLK3 SELF-LEVELLING LASER LEVEL KIT (3 PIECE)

Designed for use where a constant level or repeat level measurements are required. Applications include alignment of windows, dado rails, kitchen units, stairs, outdoor levelling etc. Class 2 laser projects a horizontal, vertical or cross beam lines on surfaces. Accuracy 0.5mm per 1m = 0.029° within the operating distance of 3-8M. Self-levelling range $\pm 6^\circ$. Supplied with heavy duty adjustable tripod (max. height 1.18M), rotating laser enhancement glasses and three AAA batteries. Comprehensive instruction manual included. Packed in blow mould carrying case.

Stock No.	Description
88640	Laser Level Kit
65643	Tripod
65644	Glasses
61833	Batteries (4 x AAA)

CLASS 2 LASER PRODUCT



4 LLK2 400mm ROTATING LASER LEVEL KIT

Designed for use where a constant level or repeat level measurements are required. Applications include alignment of windows, dado rails, kitchen units, stairs, outdoor levelling etc. One horizontal and vertical vial. Operating distance of 3-8M with an accuracy of 0.5mm per 1M = 0.029° in standard position. Supplied with heavy duty adjustable tripod (max. height 1.18M), rotating base marked 360° for mounting level, laser enhancement glasses, two 90° line generating glass prisms and two AAA batteries. Supplied with manual. Packed in blow mould carrying case.

Stock No.	Description
69580	Laser Level Kit
65643	Tripod
65644	Glasses
61833	Batteries (4 x AAA)