

1 89 01

GROOVE JOINT WATERPUMP PLIERS

Manufactured to DIN ISO 8976 Specifications

Professional Quality, manufactured from chrome vanadium electric steel, oil hardened and tempered. Smoothly ground jaw faces with accurately milled five position high leverage nonslip groove joint with safety stop. No-wear pivot bolt. Teeth hardened to 61HRC. Plastic coated handles with slip guards for extra safety. Has 'no-nip' feature which prevents handles locking together and damaging users' hands. Display packed.

Stock No.	Overall Length	Holding Capacities	
		Pipes O/D dia.	Nuts (across flats)
82898	250mm	33mm	36mm

2 00 19 19 VO4

COUNTERTOP DISPLAY OF 10 250mm ALLIGATOR® WATERPUMP PLIERS

Manufactured to DIN ISO 8976 Specifications

Professional Quality, in countertop display.

Contents: 10 pairs of Stock No. 75355 250mm Alligator® Waterpump Pliers

Stock No.
05768




3 88 02 SBE

ALLIGATOR® WATERPUMP PLIERS

Manufactured to DIN ISO 8976 Specifications

Professional Quality, manufactured from chrome vanadium electric steel, oil hardened and tempered with smoothly ground jaws, joint faces and an accurately formed box joint with safety stop. Nine position adjustment. The parallelogram-shaped gripping surfaces have specially hardened teeth to 61HRC for positive grip on pipes and nuts. Heavy duty moulded handles with slip guards for extra safety. Has 'no-nip' feature which prevents handles locking together and damaging users' hands. Display packed.

Stock No.	Overall Length	Holding Capacities	
		Pipes O/D dia.	Nuts (across flats)
88148	250mm	50mm	46mm
88150	300mm	70mm	60mm



4 88 01

ALLIGATOR® WATERPUMP PLIERS (DISPLAY PACKED)

Manufactured to DIN ISO 8976 Specifications

Professional Quality, manufactured from chrome vanadium electric steel, oil hardened and tempered with smoothly ground jaws, joint faces and an accurately formed box joint with safety stop. The parallelogram-shaped gripping surfaces have specially hardened teeth to 61HRC for positive grip on pipes and nuts. Plastic coated handles with slip guards for extra safety. Has 'no-nip' feature which prevents handles locking together and damaging users' hands.

Stock No.	Overall Length	Holding Capacities	
		Pipes O/D dia.	Nuts (across flats)
59812	180mm	42mm	36mm
10954	250mm	50mm	46mm
81189	300mm	70mm	60mm
34182	400mm	90mm	95mm



5 88 01

ALLIGATOR® WATER PUMP PLIERS (SOLD LOOSE)

Stock No.	Overall Length	Holding Capacities	
		Pipes O/D dia.	Nuts (across flats)
75355	250mm	50mm	46mm
75354	300mm	70mm	60mm

HOSE CLAMP PLIERS

Fitted with rotating jaws which tightly secure the hose clamps shown on the right, allowing for safe removal even within difficult to access areas like engines.



6 85 51 250

250mm HOSE CLAMP PLIERS

DRAPERTOOLS.COM/DRAPTIV

Manufactured to DIN ISO 8976 Specifications

Professional Quality, exceptionally versatile hose clamp pliers fitted with rotating grip inserts. Used for removing spring band rings, standard or space saving clamps and simple spring wire hose clamps found in older vehicles and household appliances. The quick-set 25 position adjustment provides easy alteration for precise and repetitive working, useful when working with reinforced or very large spring band clamps. Display packed.

Stock No.	Length
38389	250mm