Lighting & Sockets

Door switch, ADSW

Description: Door switch to activate any electrical device (lighting, signalling, alarms,

etc.) designed for wall mounted enclosures. Cable entry M20. I

n stainless steel enclosures, machining is required.

Switch capacity:

CE, EAC, UL_recognized. Approvals:

1 piece with mounting accessories. Pack quantity:

> Item no. ADSW01



















Power socket with integrated fuse, LPS

Description: DIN rail mounted electrical socket. Pressure clamp connection for easy

and quick wiring.

92 mm x 62 mm x 48 mm. Dimensions:

Connection: 3 pressure clamps for stranded and rigid wire 0.5-2.5 $\mbox{mm}^2.$ Integrated

fuse 6,3,A 5x20 mm.

Finish: Light grey.

Material: Plastic UL 94 V-0.

Pack quantity: 1 piece.





General Accessories

Profiles



DIN rails, PP

Description: According to EN 60715. Material: Galvanized steel.

 15×2 m. Pack quantity:

Description	Туре	Hole pattern	Dim	Item no.
With holes	Omega	Hole pattern 18 x 5.2 mm	5 x 15	PP0515H
Without holes	Omega		7.5 x 35	PP0735
With holes	Omega	Hole pattern 18 x 5.2 mm	7.5 x 35	PP0735H
Without holes	G		15 x 32	PP1532
With holes	G	Hole pattern 18 x 5.2 mm	15 x 32	PP1532H
Without holes	Omega		15 x 35	PP1535
With holes	Omega	Hole pattern 18 x 5.2 mm	15 x 35	PP1535H



Support bracket, DRS

Description: Mounting brackets to install earthing strips and rails.

Material: Zinc plated steel.

Inclined

rack qualitity.	20 pieces.	
Т	ype	Item no.
Fla	at	DRS20F

DRS20I



Mounting rails, CP

Installation profile with and without 25 mm hole pattern. Add GLM Description:

sliding nuts for easy installation of components.

Material: Galvanized steel. 10 x 2 m.

Description	Dim	Item no.		
With holes	10 x 20	CP1020		
Without holes	10 x 20	CP1020U		
With holes	20 x 20	CP2020		
Without holes	20 x 20	CP2020U		
With holes	20 x 40	CP2040		
Without holes	20 x 40	CP2040U		



SUBJECT TO CHANGE WITHOUT NOTICE 578 PRODUCT CATALOGUE hoffman.nVent.com | www.eldon.com hoffman.nVent.com | www.eldon.com PRODUCT CATALOGUE 579