

AFS08083

STAINLESS STEEL SINGLE DOOR WITH INTEGRATED RAIN HOOD ENCLOSURE



With mounting plate

D	300
Degree of slope	11°
H	800
N° of locks	2
Item no.	AFS08083
Part No. AISI 304	AFS08083
Part No. AISI 316L	AFS08083-316*
Usable depth	280
W	800
d	280
h	750
w	750
Item no.	AFS08083

Material: AISI 304 / AISI 316L pre-grained stainless steel. Body: 1.5 mm. Door: 1.5 mm / 2 mm for enclosures with a height of 1000 mm or greater. Mounting plate: 2 mm galvanized steel.

Body: The top of the body is equipped with a sloping roof at an angle of between 8 and 20 degrees sloping towards the front, giving a 10 mm overhang to remove any liquids away from the door. Folded and seam welded.

Door: Corner formed in one piece. Surface mounted with 130° opening. Concealed AISI 304 stainless steel hinges with captive pin. Can be mounted to give left or right hand opening (Machining is required). Sealing is ensured by an injected one piece silicone gasket.

Lock: Zamak double-bit 3 mm lock with 90° movement. Stainless steel lock and other locks available on request.

Mounting plate: The mounting plate is marked vertically at 10 mm intervals for easy horizontal positioning of equipment. On the top and bottom there are holes to facilitate cable fixing. Fixed onto M8 press welded studs to the rear of the enclosure. All sides from 800 mm and above are strengthened by folded edges. By using the AMG accessory the mounting plate position can be adjusted to any depth.

Cable access: No gland openings as standard.

Protection: Corresponds with IP 66 | TYPE 4X, 12, 13 | IK 10.

Finish: 240s pre grained stainless steel (average 0.5 micron).

Delivery: Enclosure with door, mounting plate, metallic key and mounting accessories.

Additional information or notes: In environments known for quick temperature changes, consideration to condensation should be taken. Please see Eldon's thermal management section.