

Floor Standing Enclosures

Steel Range

Accessories | Full height doors

Door frame mounting profiles, DCP

Description:

Horizontal profiles with 25 mm hole pattern. Fits directly onto the door frame. For easy mounting of light equipment by using CNT05 screws, hole pattern of 4.5 mm and 6.5 mm in diameter.

Material:

2 mm zinc plated steel.

Pack quantity:

20 bars with mounting accessories.

W	Item no.
400	DCP402
500	DCP502
600	DCP602
800	DCP802
1000	DCP1002



Cable conduits, CON

Description:

For flexible and safe protection of cables installed between the door or swing frame and the enclosure's interior. Highly flexible and halogen free.

Material:

Polyethylene.

Mounting requirements:

Add CONH for direct mounting to profiles.

Pack quantity:

25 m.

Diameter	Item no.
16	CON16
29	CON29
36	CON36
48	CON48



Universal conduit holders, CONH

Description:

Universal holder for cable conduit CON. Can be mounted horizontally or vertically on any 25 mm hole pattern of the door frame, enclosure frame or accessory profile.

Material:

Polycarbonate.

Pack quantity:

10 pieces.

Diameter	Item no.
16	CONH16
29	CONH29
36	CONH36
48	CONH48



Door switch, DSW

Description:

Door switch to activate any electrical device (lighting, signalling, alarms, etc.). Can be mounted after installing the enclosure thereby keeping the door opening free. Fixed on the inside hole pattern of the enclosure's frame in floor standing enclosures. Cable entry M20.

Switch capacity:

3A / 240V.

Approvals:

CE, EAC, UL-Recognized.

Pack quantity:

1 piece with mounting accessories.

Item no.
DSW01



Universal keyboard trays, UKT

Description:

Horizontal hinged keyboard tray with lateral sliding mouse pad (L.H. or R.H.). Equipped with panel stay. When the tray is folded out, the enclosure is sealed for dust ingress by a closed chamber.

Material:

1.75 mm steel plate.

Finish:

RAL 7035 structured powder coating.

Pack quantity:

1 door with hinges, lock, keyboard mounting support, mouse pad and mounting accessories.

H	W	Item no.
250	600	UKT06R5
250	800	UKT08R5



Transparent aluminium windows, ADA

Description:

Viewing window when used in combination with mounting kit ADAMK. The double-bit 3 mm lock can be replaced by any optional insert or handle. It increases the enclosure depth by 10 mm.

Material:

Aluminium and 3 mm acrylic glass.

Finish:

Anodised aluminium.

Protection:

IP 54.

Pack quantity:

1 viewing window.

For enclosure		Viewing area		N° of locks	Item no.
H	W	h	w		
300	300	226	226	1	ADA03030
400	300	326	226	1	ADA04030
400	400	326	326	1	ADA04040
400	600	326	526	1	ADA04060
500	300	426	226	1	ADA05030
500	400	426	326	1	ADA05040

