

FOOT PUMP

Heavy-duty foot pump with 450mm (approx) delivery hose, "Lock On" connector for tyres and three accessory nozzles. Foot pump locks closed for safe keeping when not in use. Pressure dial marked 0-100 psi and 0-7 bar.

Stock

22267



4430 **FOOT PUMP**

450mm (approx) delivery hose with "Lock On" connector for tyres and football inflator adaptor. Pressure dial marked 0-100 psi and 0-7kg/cm2 (0-7 bar). Display carton

Stock

14172



TYRE PRESSURE GAUGE

Hand-held dual reading gauge with flexible 250mm long hose. Swivel angled tyre connection and air release valve. Large easy-to-read scale graduated 5-100psi in increments of two psi and 0.5-6bar in increments of 0.1 bar. Display packed

Stock No.

69924

9 TPG101 **TYRE PRESSURE GAUGE** Hand-held dual reading gauge with straight push-on valve chuck. Scale graduated 0-60psi in increments of two psi and 0-4bar in increments of 0.1 bar.

Available in the following randomly supplied colours;

purple, red, blue, yellow and black. Display packed.

Stock 69923



DOUBLE CYLINDER FOOT PUMP

Heavy-duty foot pump suitable for applications where a high volume of air or fast pumping action is required. Pressure dial is marked 0-100 psi and 0-7 bar. Foot pump locks closed for safe keeping when not in use. Supplied with 600mm (approx.) delivery hose with "Lock On" connector for tyres and three accessory nozzles.

Stock No.

22269



5 4435

DOUBLE CYLINDER FOOT PUMP

Manufactured to GS Specifications

High performance, suitable for applications where a high volume of air or fast pumping action is required. Pressure dial is marked 0-100 psi and 0-7 bar. Robust all-metal design with 4mm thick steel base. Supplied with 600mm (approx.) delivery hose with "Lock On" connector for tyres etc. and three accessory nozzles. Display carton

Stock

25996



Handy-size dual-reading tyre pressure reader - range 2-99psi (±1psi) and 0.15-7.99 bar. Low power consumption with automatic shut off and powered by a 3V lithium battery (supplied). Display packed.

Stock

52304



3 DA12/250A

12V MINI ANALOGUE AIR COMPRESSOR (250psi max.)

Multi-functional compressor with flash light/torch beam and pressure dial (guide only). For the inflating of tyres, dinghies and sports equipment. Powered by cigarette lighter socket. Supplied with 12V DC car cigarette lighter plug on 3M long (approx.) lead, two inflating adaptor nozzles, one needle valve adaptor and hose clip-on tyre adaptor. Display carton.

The pressure dial on this model is for guidance only and should be checked with a tyre pressure gauge to BS EN12645:1999

Stock No.

65958





DA12/150

12V PORTABLE AIR COMPRESSOR

- Lightweight 12v DC Direct driven air compressor
- · Crocodile clips connect directly to vehicle batteries
- Perfect for portable field use
- Supplied with anti-settling base panel, On/Off pressure regulator, pressure gauge, crocodile clips, euro connector and 3 piece nozzle adaptors. Carton packed.

Specification:

Air displacement Input current Maximum pressure

... 160L/min ... 12V ... 150psi

Stock No.

66155



🔟 TVTS1 **TYRE VALVE TORQUE DRIVER**

Expert Quality, allows replacement of Schrader valve cores to the correct torque. Important on vehicles with Tyre Pressure Monitoring Systems (TPMS). Max torque 0.45Nm. Display packed.

Stock No.	Length
46795	150mm



TVRT TYRE VALVE REPAIR TOOL

Cleans internal and external valve stem threads and removes valve cores. Display packed.

Stock 51548