

Order Code: 92 SHS W

Cheriton Victorian Polished Brass Shaver Socket Dual Voltage. Standard Insert will be White.

Attributes

Primary Range Cheriton Victorian

Insrt SHS Plate material Metal Size (double) height 146mmV Size (double) width 86mm Size (double) depth 8.5mm

Box fixing hole centres 120.6mm Vertical

Minimum wall box depth 47mm Current rating 20VA Voltage 220/250V AC

200/250V input; 115/230V Max load

20VA output IP rating IP2XD

Switched Poles none Contact Gap Minimum none Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 3 x 2.5mm2

Terminal Capacity 4 2 x 4mm2 Multi-Strand

Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2

Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed **Ambient Operating** -5° to +40°C Temperature Recommended Location Indoor use only

Max installation Altitude 2000m

BS EN ISO Standard BS EN 61558 - BS 4573 Additional Notes: Must be mounted vertically Patents And Trademarks Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001: 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. กรรPlus





R. Hamilton & Co Ltd. Tel: +44 (0)1747 860088 Unit G

Fax: +44 (0)1747 861032

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

92 SHS W April 6, 2013

Page 1 of 1

Email: info@hamilton-litestat.com

E & OE

Web: www.hamilton-litestat.com