




Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.



The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.

Order Code: 90 TCS W

Cheriton Georgian Polished Brass 1 gang Telephone Slave. Standard Insert will be White.

Attributes

Primary Range Cheriton Georgian

Insrt **TCS** Plate material Metal Size (single) height 88mm Size (single) width 88mm Size (single) depth 10.8mm Box fixing hole centres 60.3mm Minimum wall box depth 25mm IP rating IP2XD

Earth Terminal Capacity 1 5 x 1mm2
Earth Terminal Capacity 2 4 x 1.5mm2
Earth Terminal Capacity 3 3 x 2.5mm2

Earth Terminal Capacity 4 1 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2

Product Class 1

Ambient Operating
Temperature

Must be earthed (ref BS7671 415.2.1)

-5° to +40°C

Recommended Location Indoor use only

Max installation Altitude 2000m

Patents And Trademarks Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. ∩**5**5Plus





R. Hamilton & Co Ltd. Tel: +44 (0)1747 860088

Unit G

Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

90 TCS W March 19, 2013

Page 1 of 1

E & OE

Web: www.hamilton-litestat.com