


www.hamilton-litestat.com





Wiring



Dimensions

74 DSAT B

Hartland Satin Steel Digital Screened Non Isolated 1 gang Satellite. Standard Insert will be Black.

| Primary Range | Hartland | |
|-------------------------------|---------------------------------------------------|--|
| Insert Type | Digital Satellite Outlets - Screened Non Isolated | |
| Plate Finish | Satin Steel | |
| Frame Finish | | |
| Switch Colour | | |
| Body & Switch Trim | Black | |
| Height | Single = 88mm | |
| Width | Single = 88mm | |
| Depth | Single = 5mm | |
| Fixing Hole Centres | Box Fixing = 60.3mmBox Fixing = 60.3mm | |
| Minimum Wall Box Depth | 35mm | |
| Wattage | | |
| Switched Poles | n/a | |
| Current Rating | | |
| Voltage | | |
| Max load | | |
| Contact Gap Minimum | n/a | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-Strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Indoor use only | |
| Standard/Approval | | |
| EuroFix Additional Notes | | |
| Frequency 1 | SAT DC=5-2200 MHz | |
| Frequency 2 | | |
| Frequency 3 | | |
| Frequency 4 | | |
| Patents and Trademarks | Trade Mark No. 2344778 | |

| All products listed conform to current British or European standards and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System. | It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
|--------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. | Correct as at August 2012 E&OE |

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary) Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire Registered in London No. 941624 • VAT Registration No. 222 6607 84







