





Order Code :  
87C R232 BC-W  
Sheer CFX Bright Chrome 3 gang 2 Way  
20AX Rocker. Standard Insert will be Bright  
Chrome with a White surround.

**Attributes**

Primary Range	Sheer CFX
Insrt	R232
Plate material	Metal
Size (double) height	86mm
Size (double) width	145mm
Size (double) depth	4.5mm
Box fixing hole centres	120.6mm
Grid fixing hole centres	Grid fixing inserts are available on Sheer CFX plates. Refer to GRID-IT Technical Pages and GRID-IT catalogue for full details.
Minimum wall box depth	25mm
Current rating	20AX
Voltage	220/250V AC
Max load	20 Amp inductive
IP rating	IP2XD
Switched Poles	Single
Contact Gap Minimum	3mm
Terminal Capacity 1	5 x 1mm <sup>2</sup>
Terminal Capacity 2	4 x 1.5mm <sup>2</sup>
Terminal Capacity 3	2 x 2.5mm <sup>2</sup>
Terminal Capacity 4	2 x 4mm <sup>2</sup> Multi-Strand
Terminal Capacity 5	1 x 6mm <sup>2</sup>
Earth Terminal Capacity 1	6 x 1mm <sup>2</sup>
Earth Terminal Capacity 2	5 x 1.5mm <sup>2</sup>
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>
Earth Terminal Capacity 4	2 x 4mm <sup>2</sup> Multi-Strand
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>
Product Class 1	Must be earthed
Ambient Operating Temperature	-5Â° to +40Â°C
Recommended Location	Indoor use only
Max installation Altitude	2000m
BS EN ISO Standard	BS EN 60669-1
Patents And Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	   

<b>R. Hamilton &amp; Co Ltd.</b>	Unit G	Quarry Industrial Estate	MERE, Wiltshire	UK BA12 6LA
Tel: +44 (0)1747 860088	Fax: +44 (0)1747 861032	Email: info@hamilton-litestat.com	Web: www.hamilton-litestat.com	