


NO IMAGE
AVAILABLE



Each coaxial cable should be connected to the appropriate terminal as shown.

This diagram applies to all unscreened non-isolated and isolated connections including diplex (TV/FM) units.

Care should be taken to ensure that the screening braid is clamped securely by the cable clamp and does not come into contact with the centre conductor.

Order Code :
MOD-SATI B

EuroFix 50X25mm Modular Satellite Isolated
Black. Standard Insert will be Black.

Attributes

Primary Range	EuroFix
Secondary Range	EuroFix Modules
Insrt	MOD-SATI
Plate material	Plastic
Minimum wall box depth	35mm
IP rating	IP2XD
Earth Terminal Capacity 1	5 x 1mm ²
Earth Terminal Capacity 2	4 x 1.5mm ²
Earth Terminal Capacity 3	3 x 2.5mm ²
Earth Terminal Capacity 4	1 x 4mm ² Multi-Strand
Earth Terminal Capacity 5	1 x 6mm ²
Product Class 1	Must be earthed (ref BS7671 415.2.1)
Ambient Operating Temperature	-5Â° to +40Â°C
Recommended Location	Indoor use only
Max installation Altitude	2000m
Additional Notes :	Note Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box phase barriers MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.
Module size (height)	50mm
Modules size (width)	25mm
Module size (depth)	24mm
EuroFix Additional Notes	Isolated F-type outlet for Satellite or Cable TV installations where a DC signal back to the LNB unit on the satellite dish NOT required.

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.



R. Hamilton & Co Ltd.

Unit G

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Tel: +44 (0)1747 860088

Fax: +44 (0)1747 861032

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com