





Order Code :

84C SPN SS-B

Sheer CFX Satin Steel 1 gang 13A Fused Spur, Double Pole + Neon. Standard Insert will be Satin Steel with a Black surround.

#### Attributes

Primary Range	Sheer CFX
Insrt	SPN
Plate material	Metal
Size (single) height	86mm
Size (single) width	86mm
Size (single) depth	4.5mm
Box fixing hole centres	60.3mm
Grid fixing hole centres	Grid fixing inserts are available on Sheer CFX plates. Refer to GRID-IT Technical Pages and GRID-IT catalogue for full details.
Minimum wall box depth	35mm
Current rating	13 Amp
Voltage	220/250V AC
Max load	13 Amp
IP rating	IP2XD
Switched Poles	Double
Contact Gap Minimum	3mm
Terminal Capacity 1	3 x 2.5mm <sup>2</sup>
Terminal Capacity 2	2 x 4mm <sup>2</sup> Multi-Strand
Terminal Capacity 3	1 x 6mm <sup>2</sup>
Earth Terminal Capacity 1	6 x 1mm <sup>2</sup>
Earth Terminal Capacity 2	5 x 1.5mm <sup>2</sup>
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>
Earth Terminal Capacity 4	2 x 4mm <sup>2</sup> Multi-Strand
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>
Product Class 1	Must be earthed
Ambient Operating Temperature	-5Â° to +40Â°C
Recommended Location	Indoor use only
Max installation Altitude	2000m
BS EN ISO Standard	BS 1363-4
Patents And Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	   

**R. Hamilton & Co Ltd.**      Unit G      Quarry Industrial Estate      MERE, Wiltshire      UK BA12 6LA  
 Tel: +44 (0)1747 860088      Fax: +44 (0)1747 861032      Email: info@hamilton-litestat.com      Web: www.hamilton-litestat.com