

www.hamilton-litestat.com

Item Image Wiring 2 Way and Intermediate Switching Wiring Methods **Dimensions** HARTLAND CFX 4 GANG 2 WAY 20AX DOLLY SWITCH Hamilton

79C T24

Hartland CFX Antique Brass 4 gang 2 Way 20AX Dolly. Standard Insert will be Antique Brass.

Primary Range	Hartland CFX	
Insert Type	2 Way Dolly/Toggle Switches	
Plate Finish	Antique Brass	
Frame Finish	Alltique blass	
Switch Colour	Antique Brass	
Body & Switch Trim	Altique blass	
Height	Double = 86mm	
Width	Double = 145mm	
Depth	Double = 145mm	
Fixing Hole Centres	Box Fixing = 120.6mmBox Fixing = 120.6mm	
Minimum Wall Box Depth	35mm	
Wattage	3311111	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Max load	20 Amp inductive	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 1	4 x 1.5mm?	
Terminal Capacity 2	2 x 2.5mm2	
Terminal Capacity 4	2 x 4mm2 Multi-Strand	
Terminal Capacity 5	1 x 6mm?	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 2	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-Strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating		
Temperature	-5° to +40°C	
Recommended Location	Indoor use only	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at August 2012 E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary) Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire Registered in London No. 941624 • VAT Registration No. 222 6607 84







