

Fluke Test Leads, Probes & Clips



Electronic Test Leads

TL910 Electronic Test Lead Set

- Very small 1 mm tips to access hard to reach test points
- Probe tip length up to 100 mm, test lead length: 1 m
- Included: 3 sets of spring loaded gold tips and 2 sets of stainless steel tips
- CAT II 1000 V, 3 A rating



TP912 Replacement Tips for TL910

- Replacement tips for TL910
- Five sets of gold plated and stainless steel tips



Fluke TL26a 5-Way Test Lead Set

1.5m, silicone-insulated leads. Rated for 30V, 8A
One red, one black.

5 ways to connect:

1. U-shaped nose for blade-shaped terminals
2. Notched jaw for gripping screw heads, bare wire or terminals
3. Serrated teeth for gripping threaded or wire-wrapped terminals
4. Cluster of sharp needles for piercing small gauge (#22-#28 AWG) wires
5. Large piercing needle for penetrating larger gauge wires



TL40 Retractable Tip Test Lead Set

- One pair (red, black) of test leads with sharp needle point tips adjustable to desired length from 0 to 76mm
- Flexible silicone insulated test leads
- CAT II 600 V, 3 A rating



TL960 Micro-Hook Test Lead Set

- 1 pair (red, black) of test leads with multi-stacking 4mm banana plugs and micro-hooks
- 90cm long PVC insulated leads
- 30 V RMS or 60 V DC, 15 A



TL950 Mini-Pincer Test Lead Set

- 1 pair (red, black) of test leads with multi-stacking 4 mm banana plugs and mini-pincers
- Mini-pincers open to 2.3mm
- 90cm long PVC insulated leads
- 30 V RMS or 60 V DC, 5 A



TL940 Mini-Hook Test Lead Set

- 1 pair (red, black) of test leads with multi-stacking 4 mm banana plugs and mini-hooks
- 90 cm long PVC insulated leads
- 30 V RMS or 60 V DC, 5 A



Patch Cords


TL930 Patch Cord Set (60 cm)

- 1 pair (red, black) multi-stacking 4 mm banana plug patch cords
- Nickel-plated banana plugs
- 60 cm long PVC insulated leads
- 30 V RMS or 60 V DC, 15 A



TL932 Patch Cord Set (90 cm)

- 1 pair (red, black) multi-stacking 4 mm banana plug patch cords
- Nickel-plated banana plugs
- 90 cm long PVC insulated leads
- 30 V RMS or 60 V DC, 15 A



TL935 Patch Cord Kit (60, 90, 120 cm)

- 3 sets (red and black pairs) of multi-stacking 4 mm banana plug patch cords
- Nickel-plated banana plugs
- 60 cm, 90 cm, 120 cm long PVC insulated leads
- 30 V RMS or 60 V DC, 15 A



Electronic Kits

TL80A-1 Basic Electronic Test Lead Kit

- One pair (red, black) each 1 metre long silicone test lead set, alligator clip and probe tip extender.
- C75 soft carrying case



TP920 Test Probe Adapter Kit

- Set of push-on adapters for TL71 and TL75 test probes
- IC test adapters, extended probe tips, medium alligator clips (max. opening 7.6 mm)
- CAT III 300 V, 5 A rating



TL970 Hook and Pincer Kit

- TL940 Mini-Hook Test Lead Set
- TL950 Mini-Pincer Test Lead Set
- TL960 Micro-Hook Test Lead Set



TL81A Deluxe Electronic Test Lead Kit

- Includes components of TL80A-1, plus one pair (red, black) each modular 1 metre long silicone test lead, test probe, hook-style and pinch style clip, alligator clip, IC probe tip adapter and spade plugs
- Quadfold soft carrying case



TLK287 Electronic Master Test Lead Kit

- Includes modular leads, probes (black and red), minigrabber/jack set, medium alligator clips (black and red), spade lug/banana jack plated (set), couplers IEC1010 (black and red), micrograbbers and -leads (black and red)
- TL910 Electronic Test Lead Set
- CAT III 1000 V (probes only)



BP980 Double Banana Plug Kit

- 5 pair (red, black) of double 4 mm banana plugs
- Each plug has 3.1 mm holes for mounting wires and components
- Brass plugs/jack, beryllium copper springs
- 30 V RMS or 60 V DC, 15 A



Industrial Test Leads

TL71 Premium Test Lead Set

- One pair (red, black) comfort grip probes with silicone insulated, right-angle test leads
- Recommended for μ V measurements
- CAT II 1000 V, 10 A rating
- CAT III 1000 V, CAT IV 600 V with protective cap



TL75 Hard Point™ Test Lead Set

- One pair (red, black) comfort grip probes with 48 inches PVC insulated, test leads with right-angle shrouded banana plugs
- Recommended for general purpose measurements
- CAT II 1000 V, 10 A rating
- CAT III 1000 V, CAT IV 600 V only with protective cap



TL76 All-in-one Test Lead Set

- One pair (red, black) 1.5 metre long silicone test leads with right angle shrouded banana plug
- Lantern tip (removable) for use with European wall sockets (4 mm $\varnothing$)
- Lantern tip can be removed for easy access to terminal blocks (2 mm $\varnothing$)
- Removable, insulated IC caps allow robing on closely spaced leads and compliance with GS38
- CAT II 1000 V, 10 A rating
- CAT III 1000 V, CAT IV 600 V only with protective cap

