

**Conductor markers**  
**TM 202/30 V0**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

**General ordering data**

|            |                                                                                  |
|------------|----------------------------------------------------------------------------------|
| Type       | TM 202/30 V0                                                                     |
| Order No.  | <a href="#">1874760000</a>                                                       |
| Version    | Conductor markers, 30 x 5 mm, PVC, Colour: Transparent, Conductor O.D.: 2 - 4 mm |
| GTIN (EAN) | 4032248464548                                                                    |
| Qty.       | 500 pc(s).                                                                       |

## Conductor markers TM 202/30 V0

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |       |       |      |
|------------|-------|-------|------|
| Length     | 30 mm | Width | 5 mm |
| Net weight | 0.6 g |       |      |

### Markings

|                                   |                     |                                   |                     |
|-----------------------------------|---------------------|-----------------------------------|---------------------|
| Colour                            | Transparent         | Conductor O.D.                    | 2 - 4 mm            |
| Conductor cross-section, max.     | 2.5 mm <sup>2</sup> | Conductor cross-section, min.     | 0.5 mm <sup>2</sup> |
| Halogen                           | Yes                 | Material                          | PVC                 |
| Operating temperature range, max. | 80 °C               | Operating temperature range, min. | -40 °C              |
| Pin can be written (STI)          | No                  | Type of printing                  | blank               |
| UL 94 flammability rating         | V-0                 |                                   |                     |

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 2.0   | EC001530    | ETIM 3.0   | EC001530    |
| UNSPSC     | 44-12-17-08 | eClass 4.1 | 24-19-02-19 |
| eClass 5.1 | 27-14-91-03 | eClass 6.2 | 27-14-91-29 |
| eClass 7.1 | 27-14-91-29 |            |             |

### Approvals

|           |         |
|-----------|---------|
| Approvals |         |
| ROHS      | Conform |