

References

VM1 switch I-0-II

Rating (A)	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	IP20 ⁽²⁾ bridging bar	Auxiliary contact
63 A	3 P	4430 3006 ⁽¹⁾	Black 4439 5012	S1 type Black IP65 1413 2113	200 mm 1402 0820 320 mm 1402 0832	3 P 4499 3006 4 P 4499 4006	1 NO/NC auxiliary contact 4439 0001
	4 P	4430 4006 ⁽¹⁾					
80 A	3 P	4430 3008 ⁽¹⁾					
	4 P	4430 4008 ⁽¹⁾					
100 A	3 P	4430 3010 ⁽¹⁾					
	4 P	4430 4010 ⁽¹⁾					
125 A	3 P	4430 3012					
	4 P	4430 4012					

VM1 switch I - I+II - II

Rating (A)	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	IP20 ⁽²⁾ bridging bars
63 A	3 P	4440 3006	Black 4449 5012	S1 type Black IP65 1413 2114	200 mm 1403 0820 320 mm 1403 0832	3 P 4499 3006 4 P 4499 4006
	4 P	4440 4006				
80 A	3 P	4440 3008				
	4 P	4440 4008				
100 A	3 P	4440 3010				
	4 P	4440 4010				
125 A	3 P	4440 3012				
	4 P	4440 4012				

(1) Device available enclosed (see "Enclosed transfer switches" page 726).

(2) IP: protection index according to IEC 60529.

Accessories

Direct operation handle

Rating (A)	Switching type	Reference
63 ... 125	I - 0 - II	4439 5012
63 ... 125	I - I+II - II	4449 5012



access_111_a_1_cat

External operation handle

Use

Door interlocked external front operation handles include an escutcheon, are padlockable and must be utilised with an extension shaft.

Rating (A)	Switching type	Padlockable	External IP ⁽¹⁾	Reference
63 ... 125	I - 0 - II	1 position	IP55	1411 2113
63 ... 125	I - 0 - II	1 position	IP65	1413 2113
63 ... 125	I - 0 - II	3 positions	IP65	1413 2813
63 ... 125	I - I+II - II	1 position	IP65	1413 2114
63 ... 125	I - I+II - II	3 positions	IP65	1413 2814

(1) IP: protection index according to IEC 60529.



access_149_a_2_cat

Type S handle adapter

Use

Enables S-type handles to be fitted in place of existing older style SOCOMEC handles. Adapter can also be utilised as a spacer to increase the distance between the panel door and the handle lever. Dimensions: adds 12 mm to the depth of the handle.

Colour	To be ordered in multiples of	External IP ⁽¹⁾	References
Black	1	IP65	1493 0000

(1) IP: protection index according to IEC 60529.



access_187_a_2_cat

Alternative S-type handle covers

Colour	To be ordered in multiples of	Reference
Light grey	50	1401 0001
Dark grey	50	1401 0011

Use

For single lever type S1 handles. Other colours available: consult us.



access_198_a_1_cat