



Triple Turn TE Type (PLT)




Compact TE fluorescent lamps used in commercial luminaires such as downlights, bulkheads, pendants and many other applications.

- 10,000 hour life
- 3500K white or 4000K cool white colour options
- 85/1B colour rendering index/group
- SPECTRA-PLUS Triphosphor coated for excellent colour rendering, high output and longer life
- Suitable for use in emergency luminaires
- Not suitable for dimming
- To be used with external starter or electronic ballast
- Internally fused for safety



Product Code	Watts (W)	Volts (V)	Cap	Colour Appearance	Colour Temp (K)	Initial Lumens (lm)	Dimensions (mm)		Energy Rating	Order Qty
							Dia	H		
Single Carton										
CLTE13SW	13	240	Gx24q-1 4 Pin	White	3500	900	49	104		10
CLTE13SCW	13	240	Gx24q-1 4 Pin	Cool White	4000	900	49	104		10
CLTE18SW	18	240	Gx24q-2 4 Pin	White	3500	1200	49	110		10
CLTE18SCW	18	240	Gx24q-2 4 Pin	Cool White	4000	1200	49	110		10
CLTE26SW	26	240	Gx24q-3 4 Pin	White	3500	1800	49	125		10
CLTE26SCW	26	240	Gx24q-3 4 Pin	Cool White	4000	1800	49	125		10
CLTE32SW	32	240	Gx24q-3 4 Pin	White	3500	2200	49	141		10
CLTE32SCW	32	240	Gx24q-3 4 Pin	Cool White	4000	2200	49	141		10
CLTE42SW	42	240	Gx24q-4 4 Pin	White	3500	3100	49	163		10
CLTE42SCW	42	240	Gx24q-4 4 Pin	Cool White	4000	3100	49	163		10

99



Gx24q-1 4 Pin Cap Gx24q-2 4 Pin Cap Gx24q-3 4 Pin Cap

