

LOADSTAR DISTRIBUTION BOARDS



18LS08MR Integral Metering option



100SW2

18R63/30/4

125A TP 'METER READY' TYPE B DISTRIBUTION BOARD

No of Ways	H	W	D	Surface List No.
4	490	430	155	18LS04MR
6	570	430	155	18LS06MR
8	650	430	155	18LS08MR
12	815	430	155	18LS12MR
16	895	430	155	18LS16MR
20	1000	430	155	18LS20MR
24	1140	430	155	18LS24MR

No of Ways	H	W	D	Flush List No.
4	540	430	155	18LF04
6	620	430	155	18LF06
8	700	430	155	18LF08
12	865	430	155	18LF12
16	945	430	155	18LF16
20	1025	430	155	18LF20
24	1190	430	155	18LF24

No of Ways	H	W	D	with DIN Section List No.
4	650	430	155	18LS04D
8	845	430	155	18LS08D
12	975	430	155	18LS12D
16	1140	430	155	18LS16D
20	1140	430	155	18LS20D

- DIN rail to accommodate up to 18 modules of control devices Contactor, Timer etc. with DIN section models

ADD-ON 12W LOADSTAR 'L' BOARD

No of Ways	H	W	D	List No.
12	675	430	155	18LS12A
Vertical connection kit				18LK12V

- 18LS12A 'Add-on' Board is designed to fit above 16, 20 & 24 way 'L' Boards, to create 28, 32 & 36 way TP Boards
- 18LK12V kit connects 18LS12A to 16, 20 & 24 way Boards

LOADSTAR 125A INCOMING OPTIONS

Order Device and Kit (where required) separately.

Switch Disconnector, modular (50mm ²)	Device	Kit
40A TP	40SW3	
63A TP	63SW3	None
100A TP	100SW3	Required
125A TP	125SW3	
40A 4P	40SW4	18LK125
63A 4P	63SW4	18LK125
100A 4P	100SW4	18LK125
125A 4P	125SW4	18LK125
100A DP (TP to SP conversion)	100SW2	18LKTPSP
125A DP (TP to SP conversion)	125SW2	18LKTPSP

RCCB (35mm ²)	Device	Kit
40A 4P 30mA	18R40/30/4	18LK125
40A 4P 100mA	18R40/100/4	18LK125
40A 4P 300mA	18R40/300/4	18LK125
63A 4P 30mA	18R63/30/4	18LK125
63A 4P 100mA	18R63/100/4	18LK125
63A 4P 300mA	18R63/300/4	18LK125
100A 4P 30mA	18R100/30/4	18LK125
100A 4P 100mA	18R100/100/4	18LK125
100A 4P 300mA	18R100/300/4	18LK125
100A 4P 100mA Time Delay	241/100TD	18LK125
100A DP 30mA	18R100/30/2	18LKTPSP
100A DP 100mA	18R100/100/2	18LKTPSP
100A DP 100mA Time Delay	18R100/100/2TD	18LKTPSP

Special oversize Incoming Cable connection kit for use with TP Sw Disc above.

Accommodate up to 120mm² TP Sw Disc only.		18LKD120
Direct Connection	Device	Kit
Incoming Cable Connection (50mm²)	18LKD50	
Outgoing Cable Connection Kit/Shroud (50mm²) (Set of 3 Cable Clamps + Shroud)	18LKD70	None Required