

LOADSTAR 125A INCOMING OPTIONS & ACCESSORIES



18LS212MR

250A TP TYPE B DISTRIBUTION BOARDS 'METER READY' SURFACE

No of Ways	H	W	D	List No.
4	768	430	155	18LS204MR
6	822	430	155	18LS206MR
8	876	430	155	18LS208MR
12	984	430	155	18LS212MR
16	1092	430	155	18LS216MR
20	1200	430	155	18LS220MR
24	1308	430	155	18LS224MR

SWITCH DISCONNECTORS DIRECT CONNECTION & MCCB INCOMERS

Switch Disconnector	List No
250A* 3P	250TPSD
150mm² Terminal capacity * Derated to 225A when used as an incomer to MCB distribution boards.	
Direct Connection	
250A 3P	250TPDC
120mm² Terminal capacity - All Incomers are supplied complete with mounting kit, links & fixing screws	
200A 3P MCCB	200TPMB
185mm² terminal capacity - All Incomers are supplied complete with mounting kit, links & fixing screws - IEC 60947-2, EN 60947-2	



DINRAIL, ROWBOARD, SERVICE CENTRES

Rowboard:

- Suitable for 'Stand-Alone' use or 'Add-On' above surface 'L' type board.
- Each row will accommodate 18 off 18mm module wide DIN Rail mounted devices.
- Main Neutral and Earth Bars included, along with provision for additional 'Mini' Neutral and Earth bars.

No of Rows	H	W	D	Surface
1	245	430	155	18AS1
2	410	430	155	18AS2
3	570	430	155	18AS3
4	735	430	155	18AS4
5	815	430	155	18AS5

Service Centre/DIN Rail Board:

- 'Add-On' for fixture above or below surface 'L' Type board.
- Equipped with easily removed DIN Rail to accommodate 18 or 36, 18mm module wide DIN Rail mounted devices
- 245mm & 410mm high

18 Module	18DIN18
36 Module (2 Rows of 18)	18DIN36

Cable Spreader Box

Add on Enclosure, 245mm high, Blank front cover plate	18SB
---	-------------

INDIVIDUAL ENCLOSURES

	H	W	D	Insulated
2 Modules wide	152	63	63	18GP2S
4 Modules wide	152	79	61	18GP4S
	H	W	D	Metalclad
2 Modules wide	225	90	67	18GP2M
4 Modules wide	317	136	82	18GP4M