



PRODUCT DESCRIPTION

Crabtree Weatherseal accessories are a safe, effective and innovative addition to the outdoor environment. All have been tested to British Standards and their specialist design maintains product IP rating even when in operation. Enclosure lids are automatically retained in the open position for ease of use and can be pushed firmly to click in place to provide optimal water protection.

BRITISH STANDARDS

- All Crabtree 13A Weatherseal Sockets have been type tested to BS 1363-2
- All Crabtree Weatherseal (including grid) Switches have been type tested to BS EN 60669-1
- All Crabtree Weatherseal FCUs have been type tested to BS 1363-4

TECHNICAL SPECIFICATION

Product Standard:	BS 1363-2, BS 1363-4, BS EN 60669-1
Voltage:	250V AC 50Hz
Current Rating:	13 Amps (socket outlets & FCU) 10AX (grid) 20AX (switches & grid) 10A (grid) 20A (switches & grid)
Cable Strip Length:	10mm
Ambient Temperature:	-5 to 40°C
Installation Altitude:	2000 metres
Other Marking Standards:	CE
Recommended Torque Setting:	0.5Nm L,N, E Terminals
Terminal Capacity L & N:	3 x 2.5mm ² , 2 x 4mm ²
Terminal Capacity E:	3 x 2.5mm ² , 2 x 4mm ²

RANGE PORTFOLIO

Product:	1-2 Gang 2 way switches	
	1-2 Gang DP sockets	
	13A FCU	
IP Rating:	IP56 (IP66 available for socket outlets)	
Printing:	Product marking service available on request	
Material:	ASA - Acylate Styrene Acrylonitrile	
Accessories:	Enclosure for grid	1 Gang 9731
		2 Gang 9732
		3 Gang 9733
		4 Gang 9734
	Enclosure for data	1 Gang 2 modules 9722
		2 Gang 4 modules 9724